

PERFORMANCE™ SERIES

40MBCAQ CASSETTE



Performance™ Cassette

FEATURES

- Modes: Cool, Heat, Dry, Fan, Auto, Turbo
- Louver control (fixed or swing)
- Outside air intake
- Built-in condensate lift pump
- *Follow Me* (senses temperature at handheld remote)
- Heating setback (46° F Heating Mode)
- Quiet indoor operation
- Anti-corrosive fin coating

COMPATIBLE WITH:

- 38MBRC Outdoor Unit (p 66)

Performance
SERIES

Sizes: 36 / 48

Select sizes are ENERGY STAR® certified based on indoor pairings

KEY FEATURES

Easier Service & Installation

The cassette is supplied with a condensate lift pump that is capable of lifting the water 29.5in. (750mm.) above the top of the unit.

Seamless Connection

Optimized Wi-Fi® connectivity means fewer installation steps for faster, more seamless connections.

Enhanced Design

A new, ergonomic design and larger vents for improved airflow means greater comfort from an unobtrusive indoor unit.

CONTROLS

Wireless Remote Controller included with indoor unit

Optional Wired Remote Controller KSACN0101AAA (timer function)

Optional Wired Remote Controller KSACN0701AAA (7 day programmable)



**Wireless
Remote Controller**



**Optional Wired
Controller
(7-Day Programmable)
KSACN0701AAA**

PERFORMANCE™ SERIES 40MBCAQ CASSETTE

SPECIFICATIONS:

40MBCAQ Cassette			
Heat Pump			
System			
Size		36	48
Indoor Model		40MBCAQ36XA3	40MBCAQ48XA3
Electrical			
Voltage, Phase, Cycle	V/Ph/Hz	208/230-1-60	208/230-1-60
Power Supply		Indoor Unit Powered From Outdoor Unit	
MCA	A	1.0	1.5
Controls			
Wireless Remote Controller (° F / ° C Convertible)		Standard	Standard
Wired Remote Controller (° F / ° C Convertible)		Optional	Optional
Operating Range			
Cooling Indoor DB Min - Max	° F (° C)	60.8~90 (16~32)	60.8~90 (16~32)
Heating Indoor DB Min - Max	° F (° C)	32~86 (0~30)	32~86 (0~30)
Piping			
Pipe Connection Size - Liquid	in (mm)	3/8 (9.52)	3/8 (9.52)
Pipe Connection Size - Suction	in (mm)	5/8 (15.9)	5/8 (15.9)
Indoor			
Body Unit Width	in (mm)	32.68 (830)	32.68 (830)
Body Unit Height	in (mm)	9.65 (245)	11.3 (287)
Body Unit Depth	in (mm)	32.68 (830)	32.68 (830)
Body Net Weight	lbs (kg)	59.97 (27.2)	64.59 (29.3)
Panel Unit Width	in (mm)	37.4 (950)	37.4 (950)
Panel Unit Height	in (mm)	2.17 (55)	2.17 (55)
Panel Unit Depth	in (mm)	37.4 (950)	37.4 (950)
Panel Net Weight	lbs (kg)	11.02 (5)	11.02 (5)
Number of Fan Speeds		4	4
Airflow (lowest to highest)	cfm	753/853/947/1041	935/1059/1171/1288
Sound Pressure (lowest to highest)	dB(A)	46/49/51/53	49/52/54/56
Air Throw Data	ft (m)	16.4 (5)	16.4 (5)
Moisture Removal	Pint/h (L/h)	8.5 (4.0)	12.3 (5.8)
Field Drain Pipe Size O.D.	in (mm)	1 (25.4)	1 (25.4)

Performance may vary based on the Outdoor unit matched to. See compatible Outdoor Units pages for Performance Data

COMPATIBILITY:

Indoor Unit	40MBCAQ36XA3	40MBCAQ48XA3
Outdoor Unit	38MBRCQ36AA3	38MBRCQ48AA3