

INDOOR UNITS

Floor exposed (non-ducted)



Capacities 6,000 to 15,000 Btu/hr

Controller options



Floor Exposed indoor units have a slim-line design compatible with the style of the room.

Key Features

- 8.7-inch (220 mm) depth preserves room space
- 24.8-inch height leaves ample window space
- Ideal for perimeter zone air conditioning
- Setback temperature control
- Sensor enables remote reading of air supply temperature
- Auxiliary/emergency heater control
- Cooling and heating auto-changeover dual-setpoint control

Tonnage				0.5		0.7		1.0		1.3	
Floor Exposed Indoor Unit Model #				HIFE006B21S		HIFE008B21S		HIFE012B21S		HIFE015B21S	
Indoor Unit Power Supply				AC 1Phase, 208/230V, 60Hz							
Nominal Cooling Capacity ¹		Btu / h (kW)		6,000	(1.8)	8,000	(2.3)	12,000	(3.5)	15,000	(4.4)
Nominal Heating Capacity ¹		Btu / h (kW)		6,700	(2.0)	9,000	(2.6)	13,500	(4.0)	17,000	(5.0)
Sound Pressure Level ² (Overall A Scale) (Hi-Me-Lo)		dB		39-33-29		39-33-29		43-35-32		48-43-36	
Outer Dimensions	Height	in.	(mm)	24-13/16	(630)	24-13/16	(630)	24-13/16	(630)	24-13/16	(630)
	Width	in.	(mm)	41-1/8	(1045)	41-1/8	(1045)	46-1/16	(1170)	55-7/8	(1420)
	Depth	in.	(mm)	8-11/16	(220)	8-11/16	(220)	8-11/16	(220)	8-11/16	(220)
Net Weight		lbs. (kg)		61	(28)	61	(28)	68	(31)	79	(36)
Refrigerant				R410A							
Indoor Fan	Airflow Rate (Hi-Me-Lo)	cfm		300-247-212		300-247-212		424-353-318		565-494-388	
		(m ³ /min)		(8.5-7-6)		(8.5-7-6)		(12-10-9)		(16-14-11)	
Motor Nominal Output		W		20		20		28		45	
Connections											
Refrigerant Piping				Flare-Nut Connection (with Flare Nuts)							
	Liquid Line	in.	(mm)	1/4	(6.35)	1/4	(6.35)	1/4	(6.35)	1/4	(6.35)
	Gas Line	in.	(mm)	1/2	(12.70)	1/2	(12.70)	1/2	(12.70)	1/2	(12.70)
Condensate Drain	OU	in.	(mm)	1-1/4	(32)	1-1/4	(32)	1-1/4	(32)	1-1/4	(32)

NOTES:

1. Nominal capacity conditions are based on AHRI standard. Visit www.ahrinet.org for more information.
2. The sound pressure level is based on the following conditions: 4.9 ft. (1.5m) beneath the units. The above data was measured in an anechoic chamber so that reflected sound should be taken into consideration in the field.

Floor Exposed

Compatible Accessories	HIFE006-015B21S
Infrared (IR) Receiver Kit	CWDIRK01
3-Pin Connector Cable	PCC-1A
Connector Cable for Auxiliary Heater	PCC-CN1925-H
Relay and 3-Pin Connector Kit	PSC-5RA
Remote Sensor (Control)	THM-R2A