

PLA-M R32

4-Way Blow Ceiling Cassette System

Standard Inverter Heat Pump (Three Phase)



The cost effective **PLA-M Standard Inverter** range is a ceiling cassette system that blends a host of outstanding features with a sophisticated, streamlined design. Offering advanced control options and quiet operation, this range provides extreme flexibility and ease of installation, alongside energy monitoring (via PAR-41MAA controller) as standard.

Key Features & Benefits

- Increased comfort levels through advanced airflow and smart defrost features (size 100-140)
- 14°C set point option; ideal for applications where a specialist ambient condition is required (size 100-140; requires PAR-41MAA or PAR-SL101A-E controller)
- Optional 3D Total Airflow casement to allow 360° directional delivery of air (size 100-140; requires PAR-41MAA or PAR-SL101A-E controller)
- Optional 3D i-see sensor grille provides energy efficient, customised comfort by automatically monitoring room occupancy, position and body temperatures (PLP-6EAE)
- Optional filter-lowering operation, down to 4m (PLP-6EAJ)
- Optional black (Satin finish) grille (PLP-6EA-B), for environments that desire a premium quality feel
- Optional V Blocking filter provides in-room air purification, neutralising viruses, allergens, dust and mould
- Compatible with Plasma Quad Connect - an innovative, bolt-on air purifying device which neutralises viruses, bacteria, allergens, PM2.5, mould and dust. For more information, please refer to page 1.1.7

R32

PLA-M - INDOOR UNITS		PLA-M100EA2	PLA-M125EA2	PLA-M140EA2
CAPACITY (kW)	Heating (nominal)	11.2 (2.8-12.5)	13.5 (4.1-15.0)	15.0 (4.2-15.8)
	Cooling (nominal)	9.5 (4.0-10.6)	12.1 (5.8-13.0)	13.4 (5.8-14.1)
	Heating (UK)	9.63 (2.41-10.75)	11.49 (3.49-12.77)	12.77 (3.57-13.45)
	Cooling (UK)	8.65 (3.64-9.65)	11.01 (5.28-11.83)	12.19 (5.28-12.83)
SHF (nominal)		0.77	0.72	0.70
COP / EER (nominal)		3.71 / 3.50	3.71 / 3.01	3.41 / 2.70
SCOP (ηsh) / SEER (ηsc) (BS EN14825)		4.60 / 7.00	4.1 (162%) / 5.6 (231.9%)	4.1 (161.3%) / 5.7 (232.7%)
ErP ENERGY EFFICIENCY CLASS Heating/Cooling		A++ / A++	A+ / A+	A+ / A+
AIRFLOW (l/s) Lo-Mi-Mi2-Hi		317-383-433-483	350-417-467-517	400-433-483-533
PIPE SIZE mm (in) Gas/Liquid		15.88 (5/8") / 9.52 (3/8")	15.88 (5/8") / 9.52 (3/8")	15.88 (5/8") / 9.52 (3/8")
SOUND PRESSURE LEVEL (dBA) Lo-Mi-Mi2-Hi		31-34-37-40	33-37-41-44	36-39-42-44
SOUND POWER LEVEL (dBA)		61	65	65
DIMENSIONS (mm)	Width x Depth x Height (Grille)	840 (950) x 840 (950) x 298 (40)	840 (950) x 840 (950) x 298 (40)	840 (950) x 840 (950) x 298 (40)
	Unit / Panel	24 / 5	26 / 5	26 / 5
ELECTRICAL SUPPLY		Fed by Outdoor Unit	Fed by Outdoor Unit	Fed by Outdoor Unit
FUSE RATING (BS88) - HRC (A)		6	6	6
INTERCONNECTING CABLE No. Cores		4	4	4
GRILLE REFERENCE		PLP-6EA	PLP-6EA	PLP-6EA
WIRED REMOTE CONTROLLER REFERENCE		PAR-41MAA	PAR-41MAA	PAR-41MAA
WIRELESS REMOTE CONTROLLER REFERENCE		PAR-SL101A-E	PAR-SL101A-E	PAR-SL101A-E
PUZ-M - OUTDOOR UNITS		PUZ-M100YKA2 ^③	PUZ-M125YKA2 ^③	PUZ-M140YKA2 ^③
SOUND PRESSURE LEVEL (dBA)	Heating/Cooling	51 / 54	54 / 56	55 / 57
	Cooling	70	72	73
WEIGHT (kg)		78	85	85
DIMENSIONS (mm) Width x Depth x Height		1050 x 330 x 981	1050 x 330 x 981	1050 x 330 x 981
ELECTRICAL SUPPLY		380-415v, 50Hz	380-415v, 50Hz	380-415v, 50Hz
PHASE		Three	Three	Three
SYSTEM POWER	Heating/Cooling (nominal)	3.01 / 2.71	3.63 / 4.01	4.39 / 4.96
	Heating/Cooling (UK)	2.71 / 2.50	3.27 / 3.33	3.59 / 4.12
STARTING CURRENT (A)		3.5	4.9	4.9
SYSTEM RUNNING CURRENT (A) Heating/Cooling [MAX]		4.7 / 4.2 [11.5]	5.6 / 6.3 [11.5]	6.9 / 7.8 [11.5]
FUSE RATING (BS88) - HRC (A)		16	16	16
MAINS CABLE No. Cores		5	5	5
MAX PIPE LENGTH (m)		55	65	65
MAX HEIGHT DIFFERENCE (m)		30	30	30
CHARGE REFRIGERANT (kg) / CO ₂ EQUIVALENT (t)	R32 (GWP 675) - 30m	3.10 / 2.09	3.60 / 2.43	3.60 / 2.43
MAX ADDITIONAL REFRIGERANT (kg) / R32 (GWP 675) CO ₂ EQUIVALENT (t)		4.10 / 2.77	5.00 / 3.38	5.00 / 3.38

③ Three Phase

Accessories

Indoor Units

PLP-6EA

Grille for PLA-M100-140EA2

PLP-6EA-B

Black grille (Satin finish) for PLA-M100-140EA2

PLP-6EAE

3D i-see sensor grille for PLA-M100-140EA2

PLP-6EAJ

Self elevating grille for PLA-M100-140EA2

PAC-SE1ME-E

Corner panel with i-see sensor for PLA-M100-140EA2

PAR-SE9FA-E

Corner panel with signal receiver for PLA-M100-140EA2

PAC-SJ37SP-E

Shutter plate for PLA-M100-140EA2

PAC-SJ41TM-E

Multi-function casement for PLA-M100-140EA2

PLP-U160ELR-E

3D Total Airflow casement for PLA-M100-140EA2

PAC-SK36HK-E

Insulation kit (14°C cooling) for PLA-M100-140EA2

PAC-SJ39HR-E

Power supply kit for PLA-M100-140EA2

PAR-SL101A-E

Wireless remote controller for PLA-M100-140EA2

PAC-SH59KF-E

High efficiency filter for PLA-M100-140EA2

PAC-SK53KF-E

V Blocking air purifying filter for PLA-M100-140EA2

PAC-SK51FT-E

Plasma Quad Connect air purifying device for PLA-M100-140EA2

Outdoor Units

PAC-SH96SG

Air outlet guide for PUZ-M100-140YKA2

System Control Units

PAC-SA89TA

Remote on/off adaptor (3 wire adaptor)

PAC-SA88HA

Run/fault adaptor (5 wire adaptor)

PAC-SE41TS-E

Remote sensor

PAR-CT01MAA-SB/PB

Touch screen wired remote controller (PB=Premium Finish)

PAR-41MAA

Standard wired remote controller

MAC-5871F-E

Interface for connection to Wi-Fi MELCloud service

MELCOBEMS MINI (A1M+)

Modbus and BACnet MSTP CN105 adaptor

MELCORETAIL MINI


Retail control and input / output interface

PAC-SJ95MA

M-NET adaptor for size 100 to 140

Product Dimensions

PLA-M100/125/140EA2



PLA-M.EA*:100/125/140

M	①	②	A	B	C	D
100-140	REFRIGERANT PIPE Φ 9.52 FLARED CONNECTION 3/8F	REFRIGERANT PIPE Φ 15.88 FLARED CONNECTION 5/8F	281	298	79.5	79.5

Note: Please see page 1.3.66 for the full range of accessories.