

SFZ-M R32 Floor Mounted System

Standard Inverter Heat Pump (Single Phase)

The **SFZ-M** is a compact concealed unit providing simple, effective air conditioning for perimeter zones in offices, restaurants and retail premises. The unit is easy to install and with a depth of only 200mm, offers an unobtrusive method of delivering highly efficient air conditioning performance.

Key Features & Benefits

- Compact unit allowing for concealed installation
- Low static pressure level resulting in noise reduction
- Ideal for perimeter refurbishments and new build projects
- 0-25-40-60Pa static pressure settings available, for flexibility of design and installation



SFZ-M - INDOOR UNITS		SFZ-M25VA	SFZ-M35VA	SFZ-M50VA	SFZ-M60VA	SFZ-M71VA
CAPACITY (kW)	Heating (nominal)	3.2 (1.2-4.2)	4.1 (1.0-5.0)	6.0 (1.5-7.2)	7.0 (1.6-8.0)	8.0 (2.0-10.2)
	Cooling (nominal)	2.5 (1.5-3.2)	3.5 (0.7-3.9)	5.0 (1.1-5.6)	6.1 (1.6-6.3)	7.1 (1.9-8.1)
	Heating (UK)	2.47 (1.11-3.57)	3.57 (0.94-4.25)	5.10 (1.28-6.12)	6.29 (1.36-6.80)	6.80 (1.70-8.67)
	Cooling (UK)	2.30 (1.29-2.94)	3.22 (0.64-3.59)	4.60 (1.01-5.15)	5.61 (1.47-5.80)	6.53 (2.02-7.45)
SHF (nominal)		0.84	0.78	0.76	0.75	0.74
COP / EER (nominal)		3.61 / 3.90	3.90 / 3.50	3.71 / 3.40	3.71 / 3.30	3.71 / 3.30
SCOP / SEER (BS EN14825)		4.00 / 6.10	4.10 / 6.10	4.10 / 6.10	4.20 / 6.10	4.00 / 6.10
ErP ENERGY EFFICIENCY CLASS	Heating/Cooling	A+ / A++	A+ / A++	A+ / A++	A+ / A++	A+ / A++
AIRFLOW (l/s)	Lo-Mi-Hi	92-117-150	117-150-183	167-208-250	200-250-300	200-267-333
PIPE SIZE mm (in)	Gas	9.52 (3/8")	9.52 (3/8")	12.7 (1/2")	15.88 (5/8")	15.88 (5/8")
	Liquid	6.35 (1/4")	6.35 (1/4")	6.35 (1/4")	6.35 (1/4")	9.52 (3/8")
EXTERNAL STATIC PRESSURE (Pa)		0-25-40-60	0-25-40-60	0-25-40-60	0-25-40-60	0-25-40-60
SOUND PRESSURE LEVEL (dBA)	Lo-Mi-Hi	25-29-35	25-29-33	30-35-39	30-35-39	30-36-42
SOUND POWER LEVEL (dBA)		54	53	59	59	61
DIMENSIONS (mm)	Width x Depth x Height	700 x 200 x 615	900 x 200 x 615	900 x 200 x 615	1100 x 200 x 615	1100 x 200 x 615
WEIGHT (kg)		19	22.5	22.5	26	26
ELECTRICAL SUPPLY		Fed by Outdoor Unit	Fed by Outdoor Unit	Fed by Outdoor Unit	Fed by Outdoor Unit	Fed by Outdoor Unit
FUSE RATING (BS88) - HRC (A)		6	6	6	6	6
INTERCONNECTING CABLE No. Cores		4	4	4	4	4
WIRED REMOTE CONTROLLER REFERENCE		PAR-41MAA	PAR-41MAA	PAR-41MAA	PAR-41MAA	PAR-41MAA

SUZ-M - OUTDOOR UNITS		SUZ-M25VAR2	SUZ-M35VAR2	SUZ-M50VAR2	SUZ-M60VAR2	SUZ-M71VAR1
SOUND PRESSURE LEVEL (dBA)	Heating/Cooling	45 / 46	48 / 48	48 / 49	49 / 51	49 / 51
SOUND POWER LEVEL (dBA)	Heating/Cooling	59	59	64	65	66
WEIGHT (kg)		30	35	41	54	55
DIMENSIONS (mm)	Width x Depth x Height	800 x 285 x 550	800 x 285 x 550	800 x 285 x 714	840 x 330 x 880	840 x 330 x 880
ELECTRICAL SUPPLY		220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz
PHASE		Single	Single	Single	Single	Single
SYSTEM POWER	Heating/Cooling (nominal)	0.886 / 0.641	1.051 / 1.00	1.617 / 1.47	1.886 / 1.848	2.156 / 2.151
INPUT (kW)	Heating/Cooling (UK)	0.75 / 0.55	0.89 / 0.86	1.37 / 1.26	1.60 / 1.59	1.83 / 1.85
STARTING CURRENT (A)		3.1	5.0	5.7	7.6	10.0
SYSTEM RUNNING CURRENT (A)	Heating/Cooling [MAX]	3.7 / 3.0 [6.8]	5.0 / 4.1 [8.5]	8.0 / 7.1 [13.5]	9.3 / 8.4 [14.8]	9.5 / 9.1 [14.8]
FUSE RATING (BS88) - HRC (A)		10	16	20	20	20
MAINS CABLE No. Cores		3	3	3	3	3
MAX PIPE LENGTH (m)		20	20	30	30	30
MAX HEIGHT DIFFERENCE (m)		12	12	30	30	30
CHARGE REFRIGERANT (KG) / CO ₂ EQUIVALENT (T)	R32 (GWP 675) - 7m	0.65 / 0.44	0.90 / 0.61	1.20 / 0.81	1.25 / 0.84	1.45 / 0.98
MAX ADDITIONAL REFRIGERANT (KG) / CO ₂ EQUIVALENT (T)	R32 (GWP 675)	0.91 / 0.61	1.16 / 0.78	1.66 / 1.12	1.71 / 1.15	2.37 / 1.60

Accessories

Outdoor Units

MAC-881SG

Air outlet guide for SUZ-M25-35VAR2

MAC-882SG

Air outlet guide for SUZ-M50VAR2

MAC-886SG

Air outlet guide for SUZ-M60VAR2 / SUZ-M71VAR1

System Control Units

PAC-SA89TA

Remote on/off adaptor (3 wire adaptor)

PAC-SA88HA

Run/fault adaptor (5 wire adaptor)

PAC-SE41TS-E

Remote sensor

PAR-CT01MAA-SB/PB

Touch screen wired remote controller (PB=Premium Finish)

PAR-41MAA

Standard wired remote controller

PAR-334IF-E

Interface for M-NET, MA remote controller (PAR-41MAA / PAR-CT01MAA), on/off input and run/fault output

MAC-497IF-E

Interface for MA remote controller (PAR-41MAA / PAR-CT01MAA)

MAC-587IF-E

Interface for connection to Wi-Fi MELCloud service

MELCOBEMS MINI (A1M+)

Modbus and BACnet MSTP CN105 adaptor

MELCORETAIL MINI

Retail control and input / output interface


Product Dimensions

SFZ-M25/35/50/60/71VA


Upper View




Lower View



Front View



Side View



MODEL	A	B	C	D	E	F	G	H	J
SFZ-M25VA	700	756	802	660	7	600	50	55	848
SFZ-M35VA	900	956	1002	860	9	800	50	55	1048
SFZ-M50VA	900	956	1002	860	9	800	50	61	1048
SFZ-M60VA	1100	1156	1202	1060	11	1000	50	66	1248
SFZ-M71VA	1100	1156	1202	1060	11	1000	55	66	1248

Note: Please see page 1.3.66 for the full range of accessories.