

PEFY-WP-VMA-E

Ceiling Concealed Ducted Indoor Unit

The **PEFY-WP-VMA-E** low-height ducted indoor unit is concealed within the ceiling space and connects to the Hybrid Branch Controller, using water as the heat transfer medium. Offering unobtrusive air conditioning, the flexibility of duct layout allows airflow patterns to be arranged to suit any application.

Key Features & Benefits

- Low height allowing installation in smaller spaces - only 250mm
- Centrifugal fan minimises noise levels to as low as 23dBA (sizes 20-25) for minimal disturbance
- Wide range of external static pressure settings across entire range (35-150Pa) offers flexibility of application
- Drain pump included as standard
- CN105 connector available - connect to MELCOBEMS MINI for simple BEMS interfacing
- No refrigerant in occupied spaces, removing the need for leak detection under BS EN378
- Higher air off temperatures than standard VRF, allowing for improved comfort levels
- Compatible with Plasma Quad Connect - an innovative, bolt-on air purifying device which neutralises viruses, bacteria, allergens, PM2.5, mould and dust. For more information, please refer to page 1.1.7





INDOOR UNITS		PEFY-WP20VMA-E	PEFY-WP25VMA-E	PEFY-WP32VMA-E	PEFY-WP40VMA-E	PEFY-WP50VMA-E	PEFY-WP63VMA-E	PEFY-WP80VMA-E
CAPACITY (kW)	Heating (nominal)	2.5	3.2	4.0	5.0	6.3	8.0	10.0
	Cooling (nominal)	2.2	2.8	3.6	4.5	5.6	7.1	9.0
	UK Heating	2.5	3.2	4.0	5.0	6.3	8.0	10.0
	UK Total Cooling - Hi (Sensible)	2.00 (1.80)	2.50 (2.50)	3.20 (3.00)	4.00 (3.80)	5.00 (4.20)	6.40 (5.10)	8.10 (7.20)
	UK Total Cooling - M12	-	-	-	-	-	-	-
POWER INPUT (kW)	UK Total Cooling - M11	1.92	2.40	3.07	3.84	4.80	6.15	7.76
	UK Total Cooling - Lo	1.79	2.24	2.85	3.53	4.41	5.64	7.17
AIRFLOW (l/s)	Heating (nominal)	0.05	0.07	0.9	0.12	0.12	0.12	0.22
	Cooling (nominal)	0.07	0.09	0.11	0.14	0.14	0.14	0.24
EXTERNAL STATIC PRESSURE (Pa)	Lo-Mi-Hi	125-150-175	167-200-233	200-242-283	242-300-350	242-300-350	242-300-350	383-467-550
SOUND PRESSURE LEVEL (dBA) (50Pa)	Lo-Mi-Hi	35-50-70-100-150	35-50-70-100-150	35-50-70-100-150	35-50-70-100-150	35-50-70-100-150	35-50-70-100-150	35-50-70-100-150
WEIGHT (kg)		23-26-29	23-27-30	25-29-32	26-29-34	26-29-34	26-29-34	28-33-37
DIMENSIONS (mm)	Width	21	26	26	31	31	31	40
	Depth	700	900	900	1100	1100	1100	1400
	Height	732	732	732	732	732	732	732
ELECTRICAL SUPPLY		250	250	250	250	250	250	250
PHASE		220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz
RUNNING CURRENT (A) Heating / Cooling		Single	Single	Single	Single	Single	Single	Single
FUSE RATING (BS88) - HRC (A)		0.44 / 0.55	0.53 / 0.64	0.63 / 0.74	1.04 / 1.15	1.04 / 1.15	1.04 / 1.15	1.36 / 1.47
MAINS CABLE No. Cores		6	6	6	6	6	6	6
WATER PIPE CONNECTION		3	3	3	3	3	3	3
		3/4" BSP SCREW	3/4" BSP SCREW	3/4" BSP SCREW	3/4" BSP SCREW	3/4" BSP SCREW	1 1/4" BSP SCREW	1 1/4" BSP SCREW


Note: HVR indoor units can only be configured with the CMB-WM HBC (HVR) and PURY-(E)M YNW-A1 or PQRY-P YLM-A1 outdoor units.

Product Dimensions

PEFY-WP20/25/32/40/50VMA-E





Model	A	B	C	D	E	F	G	① Water pipe (From HBC unit)	② Water pipe (To HBC unit)
PEFY-WP20VMA-E	700	754	800	660	7	600	658	Rc3/4 screw	
PEFY-WP25.32VMA-E	900	954	1000	860	9	800	858		
PEFY-WP40.50VMA-E	1100	1154	1200	1060	11	1000	1058		



Product Dimensions

PEFY-WP63/80VMA-E



Model	A	B	C	D	E	F	G	① Water pipe (From HBC unit)	② Water pipe (To HBC unit)
PEFY-WP63VMA-E	1100	1154	1200	1060	11	1000	1058	Rc1-1/4 screw	
PEFY-WP80VMA-E	1400	1454	1500	1360	14	1300	1358		

