

PLFY-WL-VFM-E

600x600 4-Way Blow Ceiling Cassette Indoor Unit



The **PLFY-WL-VFM-E** ceiling cassette unit connects to the Hybrid Branch Controller and uses water as the heat transfer medium. Providing a smart air conditioning solution for tight ceiling spaces, and designed to fit directly into standard 600mm square ceiling grids, these units are a perfect choice for both offices and retail applications. The optional 3D i-see sensor grille optimises both energy consumption and comfort levels.


Key Features & Benefits

- Stylish square, slimline design - fits into narrow ceiling spaces with a height of only 245mm
- Low noise levels for minimal disturbance - reduced noise value with 3D turbo fan
- Enhanced airflow control through directional vanes
- Easy installation - temporary hanging hook on grille and no screw removal for corner panel / control box
- Optional 3D i-see sensor grille (SLP-2FAE) provides energy efficient, customised comfort by automatically monitoring room occupancy, position and body temperatures
- No refrigerant in occupied spaces, removing the need for leak detection under BS EN378
- Higher air off temperatures than standard VRF, allowing for improved comfort levels
- Optional V Blocking filter provides in-room air purification, neutralising viruses, allergens, dust and mould


INDOOR UNITS		PLFY-WL15VFM-E	PLFY-WL20VFM-E	PLFY-WL25VFM-E	PLFY-WL32VFM-E	PLFY-WL40VFM-E
CAPACITY (kW)	Heating (nominal)	1.9	2.5	3.2	4.0	5.0
	Cooling (nominal)	1.7	2.2	2.8	3.6	4.5
	UK Heating	1.9	2.5	3.2	4.0	5.0
	UK Total Cooling - Hi (Sensible)	1.50 (1.30)	2.00 (1.60)	2.50 (2.00)	3.20 (2.60)	4.0 (3.1)
	UK Total Cooling - Mi1	1.44	1.92	2.38	2.92	3.88
POWER INPUT (kW)	UK Total Cooling - Lo	1.36	1.89	2.26	2.52	2.98
	Heating (nominal)	0.02	0.02	0.03	0.04	0.05
	Cooling (nominal)	0.02	0.02	0.03	0.04	0.05
	AIRFLOW (Vs)	100-117-133	108-117-133	108-125-150	108-150-200	108-192-217
	SOUND PRESSURE LEVEL (dBA)	25-26-29	27-29-31	27-30-34	27-33-41	27-40-43
WEIGHT (kg)	(Grille)	13 (3)	14 (3)	14 (3)	14 (3)	14 (3)
	DIMENSIONS (mm)	570 (625)	570 (625)	570 (625)	570 (625)	570 (625)
	Depth (Grille)	570 (625)	570 (625)	570 (625)	570 (625)	570 (625)
ELECTRICAL SUPPLY	Height (Grille)	245 (10)	245 (10)	245 (10)	245 (10)	245(10)
	PHASE	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz
	PHASE	Single	Single	Single	Single	Single
FUSE RATING (BS88) - HRC (A)	RUNNING CURRENT (A)	0.18 / 0.24	0.20 / 0.26	0.23 / 0.29	0.32 / 0.38	0.40 / 0.46
	MAIN CABLE No. Cores	6	6	6	6	6
	GRILLE MODEL REFERENCE	3	3	3	3	3
WATER PIPE CONNECTION	GRILLE MODEL REFERENCE	SLP-2FA	SLP-2FA	SLP-2FA	SLP-2FA	SLP-2FA
	WATER PIPE CONNECTION	20mm I.D	20mm I.D	20mm I.D	20mm I.D	20mm I.D

Note: HVRF indoor units can only be configured with the CMB-WM HBC (HVRF) and PURY-(E)M YNW-A1 or PORY-P YLM-A1 outdoor units.

Upper View



Lower View



Side View

