

PLFY-WL-VEM-E

4-Way Blow Ceiling Cassette Indoor Unit



The **PLFY-WL-VEM-E** ceiling cassette unit connects to the Hybrid Branch Controller and uses water as the heat transfer medium. Offering 72 different airflow patterns, with the ability to handle a multitude of ceiling applications up to 4.2 metres in height, the easy to install, slimline unit is ideal for maintaining constant temperatures, thanks to adjustable vanes that allow users to precisely direct air where it's needed.


Key Features & Benefits

- Enhanced airflow control through directional vanes
- Optional 3D i-see sensor grille (PLP-6EAE) provides customised comfort by automatically monitoring room occupancy, position and body temperatures
- Optional filter lowering operation down to 4m (PLP-6EAJ), allowing for easier maintenance
- Optional black (Satin finish) grille (PLP-6EA-B), for environments that desire a premium quality feel
- No refrigerant in occupied spaces, removing the need for leak detection under BS EN378
- Higher air off temperatures than standard VRF, allowing for improved comfort levels
- Optional V Blocking filter provides in-room air purification, neutralising viruses, allergens, dust and mould
- Compatible with Plasma Quad Connect - an innovative, bolt-on air purifying device which neutralises viruses, bacteria, allergens, PM2.5, mould and dust. For more information, please refer to page 1.1.7


INDOOR UNITS		PLFY-WL32VEM-E	PLFY-WL40VEM-E	PLFY-WL50VEM-E	PLFY-WL63VEM-E	PLFY-WL80VEM-E
CAPACITY (kW)	Heating (nominal)	4.0	5.0	6.3	8.0	10.0
	Cooling (nominal)	3.6	4.5	5.6	7.1	9.0
	UK Heating	4.0	5.0	6.3	8.0	8.0
	UK Total Cooling - Hi (Sensible)	3.20 (3.20)	4.00 (3.60)	5.00 (4.20)	6.4 (5.0)	8.1 (6.1)
	UK Total Cooling - M2	3.16	3.95	4.87	6.26	7.94
	UK Total Cooling - M1	3.09	3.87	4.66	6.02	7.53
POWER INPUT (kW)	UK Total Cooling - Lo	3.02	3.77	4.39	5.73	6.95
	Heating (nominal)	0.03	0.03	0.04	0.04	0.05
AIRFLOW (l/s)	Cooling (nominal)	0.03	0.03	0.04	0.05	0.05
	Lo-M1-M2-Hi	233-250-267-283	233-250-267-283	233-267-300-333	250-283-317-350	250-300-350-383
SOUND PRESSURE LEVEL (dBA) Lo-M1-M2-Hi		26-27-29-30	26-28-29-31	27-29-31-33	27-29-31-33	27-30-33-35
WEIGHT (kg)		20	20	20	23	23
DIMENSIONS (mm)	Width (Grille)	840 (950)	840 (950)	840 (950)	840 (950)	840 (950)
	Depth (Grille)	840 (950)	840 (950)	840 (950)	840 (950)	840 (950)
	Height (Grille)	258 (40)	258 (40)	258 (40)	298 (40)	298 (40)
	Height (Grille)	258 (40)	258 (40)	258 (40)	298 (40)	298 (40)
ELECTRICAL SUPPLY		220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50/60Hz	220-240v, 50/60Hz
PHASE		Single	Single	Single	Single	Single
RUNNING CURRENT (A) Heating / Cooling		0.27 / 0.33	0.29 / 0.35	0.34 / 0.40	0.34 / 0.40	0.40 / 0.46
FUSE RATING (BS88) - HRC (A)		6	6	6	6	6
MAINS CABLE No. Cores		3	3	3	3	3
GRILLE MODEL REFERENCE		PLP-6EA	PLP-6EA	PLP-6EA	PLP-6EA	PLP-6EA
WATER PIPE CONNECTION		20mm I.D	20mm I.D	20mm I.D	22 mm (O.D)	22 mm (O.D)

Note: HVRF indoor units can only be configured with the CMB-WM HBC (HVRF) and PURY-(E)M YNW-A1 or PQRY-P YLM-A1 outdoor units.

Lower View




Front View



	A	B
32/40/50	241	258
63/80	281	298

Upper View



Side View

