

PEFY-P-VMS1-E

Ultra Thin Ceiling Concealed Ducted Indoor Unit

The **PEFY-P-VMS1-E** ceiling concealed ducted indoor unit has been designed with an ultra thin, slimline body, specifically for applications where ceiling void space is limited. With an extremely quiet operation, these units are ideal for applications such as hotel rooms.

Key Features & Benefits


- Ultra thin body allowing installation in smaller spaces - height of only 200mm & width of only 790mm (size P15-32)
- Extremely quiet operation for minimal disturbance - as low as 22dBA (size P15-20)
- External static pressure of 5-50Pa, allowing flexibility of design and application
- Available in a 1.5kW size, ideal for hotel rooms
- Compatible with Plasma Quad Connect - an innovative, bolt-on air purifying device which neutralises viruses, bacteria, allergens, PM2.5, mould and dust. For more information, please refer to page 1.1.7




INDOOR UNITS		PEFY-P15VMS1-E	PEFY-P20VMS1-E	PEFY-P25VMS1-E	PEFY-P32VMS1-E	PEFY-P40VMS1-E	PEFY-P50VMS1-E	PEFY-P63VMS1-E
CAPACITY (kW)	Heating (nominal)	1.9	2.5	3.2	4.0	5.0	6.3	8.0
	Cooling (nominal)	1.7	2.2	2.8	3.6	4.5	5.6	7.1
	UK Heating	1.9	2.5	3.2	4.0	5.0	6.3	8.0
	UK Total Cooling - Hi (Sensible)	1.50 (1.40)	2.00 (1.70)	2.50 (2.10)	3.20 (2.50)	4.10 (3.00)	5.00 (3.70)	6.40 (4.70)
	UK Total Cooling - Mi	1.44	1.89	2.32	2.99	3.95	4.78	6.13
POWER INPUT (kW)	UK Total Cooling - Lo	1.34	1.76	2.07	2.63	3.70	4.51	5.77
	Heating (nominal)	0.03	0.03	0.04	0.05	0.05	0.07	0.07
AIRFLOW (l/s)	Cooling (nominal)	0.05	0.05	0.06	0.07	0.07	0.09	0.09
	Lo-Mi-Hi	83-100-117	91-108-133	91-117-150	100-133-167	133-158-183	158-183-217	200-233-275
EXTERNAL STATIC PRESSURE (Pa)		5-15-35-50	5-15-35-50	5-15-35-50	5-15-35-50	5-15-35-50	5-15-35-50	5-15-35-50
SOUND PRESSURE LEVEL (dBA)*1 Lo-Mi-Hi		22-24-28	22-25-29	24-26-30	24-27-32	28-30-33	30-32-35	30-33-36
WEIGHT (kg)		19	19	19	20	24	24	28
DIMENSIONS (mm)	Width	790	790	790	790	990	990	1190
	Depth	700	700	700	700	700	700	700
	Height	200	200	200	200	200	200	200
ELECTRICAL SUPPLY		220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz
PHASE		Single	Single	Single	Single	Single	Single	Single
RUNNING CURRENT (A) Heating / Cooling		0.31 / 0.42	0.36 / 0.47	0.39 / 0.50	0.39 / 0.50	0.45 / 0.56	0.56 / 0.67	0.61 / 0.72
FUSE RATING (BS88) - HRC (A)		6	6	6	6	6	6	6
MAINS CABLE No. Cores		3	3	3	3	3	3	3

Note: *1 Additional sound data is available for this model. Separated inlet and breakout sound power level and discharge sound power level data is available on request.


Upper View



Front View



Side View



Model	A	B	C	D	E	F
PEFY-P15-32VMS1-E	700	752	798	660	7	600
PEFY-P40-50VMS1-E	900	952	998	860	9	800
PEFY-P63VMS1-E	1100	1152	1198	1060	11	1000