

PLFY-P-VFM-E

600x600 4-Way Blow Ceiling Cassette Indoor Unit

The **PLFY-P-VFM-E** 600x600 cassette unit provides a smart air conditioning solution for tight ceiling spaces. Designed to fit directly into standard 600mm square ceiling grids, these units are a perfect choice for both offices and retail applications. The optional 3D i-see sensor grille optimises both energy consumption and comfort levels.


Key Features & Benefits

- Stylish square slimline design - fits into narrow ceiling spaces with a height of only 245mm
- Low noise levels for minimal disturbance - reduced noise value with 3D turbo fan
- Increased comfort levels through advanced airflow
- Easy installation - temporary hanging hook on grille and no screw removal for corner panel / control box
- Optional 3D i-see sensor grille (SLP-2FAE) provides energy efficient, customised comfort by automatically monitoring room occupancy, position and body temperatures
- Optional V Blocking filter provides in-room air purification, neutralising viruses, allergens, dust and mould




INDOOR UNITS		PLFY-P15VFM-E	PLFY-P20VFM-E	PLFY-P25VFM-E	PLFY-P32VFM-E	PLFY-P40VFM-E	PLFY-P50VFM-E
CAPACITY (kW)	Heating (nominal)	1.9	2.5	3.2	4.0	5.0	6.3
	Cooling (nominal)	1.7	2.2	2.8	3.6	4.5	5.6
	UK Heating	1.9	2.5	3.2	4.0	5.0	6.3
	UK Total Cooling - Hi (Sensible)	1.50 (1.30)	2.00 (1.60)	2.50 (2.00)	3.20 (2.40)	4.00 (2.90)	5.00 (3.60)
	UK Total Cooling - Mi	1.48	1.94	2.38	3.06	3.78	4.78
POWER INPUT (kW)	UK Total Cooling - Lo	1.41	1.84	2.24	2.91	3.51	4.41
	Heating (nominal)	0.02	0.02	0.02	0.02	0.03	0.03
	Cooling (nominal)	0.02	0.02	0.02	0.02	0.03	0.03
AIRFLOW (l/s)	Lo-Mi-Hi	108-125-133	108-125-142	108-133-150	117-133-158	125-150-183	150-183-217
SOUND PRESSURE LEVEL (dBA)	Lo-Mi-Hi	26-28-30	26-29-31	26-30-33	26-30-34	28-33-39	33-39-43
WEIGHT (kg)	(Grille)	14 (3)	14 (3)	14 (3)	15 (3)	15 (3)	15 (3)
DIMENSIONS (mm)	Width (Grille)	570 (625)	570 (625)	570 (625)	570 (625)	570 (625)	570 (625)
	Depth (Grille)	570 (625)	570 (625)	570 (625)	570 (625)	570 (625)	570 (625)
	Height (Grille)	245 (10)	245 (10)	245 (10)	245 (10)	245 (10)	245 (10)
ELECTRICAL SUPPLY		220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz
PHASE		Single	Single	Single	Single	Single	Single
RUNNING CURRENT (A)	Heating / Cooling	0.14 / 0.19	0.16 / 0.21	0.17 / 0.22	0.18 / 0.23	0.23 / 0.28	0.35 / 0.4
FUSE RATING (BS88) - HRC (A)		6	6	6	6	6	6
MAINS CABLE No. Cores		3	3	3	3	3	3
GRILLE MODEL REFERENCE		SLP-2FA	SLP-2FA	SLP-2FA	SLP-2FA	SLP-2FA	SLP-2FA

Upper View



Lower View



Side View

