

MFZ-KT R32

Floor Mounted System

Inverter Heat Pump

The **MFZ-KT** floor mounted system is extremely versatile and is designed for wall-attached installation at floor level. Lightweight and compact in design, this unit is ideal for applications such as conservatories, garden rooms and small offices where wall space is limited.

Key Features & Benefits

- Lightweight, floor mounted design for easy installation
- Auto-swing vane feature provides a natural and comfortable airflow
- Controller with built-in timer
- Optional Wi-Fi interface enabling control & monitoring via the MELCloud app



MFZ-KT - INDOOR UNITS		MFZ-KT25VG	MFZ-KT35VG	MFZ-KT50VG
CAPACITY (kW)	Heating (nominal)	3.4 (1.3-4.2)	4.3 (1.1-5.0)	6.0 (1.5-7.2)
	Cooling (nominal)	2.5 (1.6-3.2)	3.5 (0.9-3.9)	5.0 (1.2-5.6)
	Heating (UK)	2.79 (1.07-3.44)	3.53 (0.9-4.10)	4.92 (1.23-5.90)
	Cooling (UK)	2.45 (1.57-3.14)	3.43 (0.88-3.82)	4.90 (1.18-5.49)
SHF (nominal)		0.79	0.70	0.72
COP / EER (nominal)		3.74 / 4.03	3.41 / 3.30	3.23 / 3.23
SCOP / SEER (BS EN14825)		4.2 / 6.5	4.4 / 6.6	4.2 / 6.8
ErP ENERGY EFFICIENCY CLASS	Heating/Cooling	A+ / A++	A+ / A++	A+ / A++
AIRFLOW (l/s)	Heating - Silent-Lo-Mi-Hi-SHi	58-67-93-122-162	58-67-93-122-162	100-128-157-193-233
	Cooling - Silent-Lo-Mi-Hi-SHi	65-80-108-130-148	65-80-108-130-148	93-112-143-173-205
PIPE SIZE mm (in)	Gas	9.52 (3/8")	9.52 (3/8")	12.7 (1/2")
	Liquid	6.35 (1/4")	6.35 (1/4")	6.35 (1/4")
SOUND PRESSURE LEVEL (dBA)	Heating/Cooling - Silent-Lo-Mi-Hi-SHi	19-23-30-37-44 / 19-24-31-37-41	19-23-30-37-44 / 19-24-31-37-41	29-35-40-44-49 / 28-32-37-42-48
SOUND POWER LEVEL (dBA)		54	54	60
DIMENSIONS (mm)	Width x Depth x Height	750 x 215 x 600	750 x 215 x 600	750 x 215 x 600
WEIGHT (kg)		14.5	14.5	15
ELECTRICAL SUPPLY		Fed by Outdoor Unit	Fed by Outdoor Unit	Fed by Outdoor Unit
FUSE RATING (BS88) – HRC (A)		6	6	6
INTERCONNECTING CABLE No. CORES		4	4	4

SUZ-M - OUTDOOR UNITS		SUZ-M25VAR2	SUZ-M35VAR2	SUZ-M50VAR2
SOUND PRESSURE LEVEL (dBA)	Heating/Cooling	46 / 45	48 / 48	49 / 48
SOUND POWER LEVEL (dBA)	Cooling	59	59	64
WEIGHT (kg)		30	35	41
DIMENSIONS (mm)	Width x Depth x Height	800 x 285 x 550	800 x 285 x 550	800 x 285 x 714
ELECTRICAL SUPPLY		220-240V, 50Hz	220-240V, 50Hz	220-240V, 50Hz
PHASE		Single	Single	Single
SYSTEM POWER INPUT (kW)	Heating/Cooling (nominal)	0.80 / 0.71	1.07 / 1.00	1.61 / 1.54
	Heating/Cooling (UK)	0.68 / 0.61	0.91 / 0.86	1.37 / 1.32
STARTING CURRENT (A)		3.7	5.0	8.0
SYSTEM RUNNING CURRENT (A)	Heating/Cooling [MAX]	3.7 / 3.0 [6.8]	5.0 / 4.1 [8.5]	8.0 / 7.1 [13.5]
FUSE RATING (BS88) – HRC (A)		10	10	20
MAINS CABLE No. CORES		3	3	3
MAX PIPE LENGTH (m)		20	20	30
MAX HEIGHT DIFFERENCE (m)		12	12	30
CHARGE REFRIGERANT (KG) / CO ₂ EQUIVALENT (T) - R32 (GWP 675) - 7M		0.65 / 0.44	0.90 / 0.61	1.20 / 0.81
MAX ADDITIONAL REFRIGERANT (KG) / CO ₂ EQUIVALENT (T) - R32 (GWP 675)		0.26 / 0.18	0.26 / 0.18	0.46 / 0.31

Accessories

Outdoor Units

MAC-881SG

Air outlet guide for SUZ-M25/35VAR2

MAC-882SG

Air outlet guide for SUZ-M50VAR2

System Control Units

PAR-CT01MAA-SB/PB

Touch screen wired remote controller (PB = Premium Finish)

PAR-41MAA

Standard wired remote controller

MAC-334IF-E

Interface for M-NET, MA remote controller
(PAR-41MAA / PAR-CT01MAA),
on/off input and run/fault output

MAC-497IF-E

Interface for MA remote controller
(PAR-41MAA / PAR-CT01MAA)

MAC-587IF-E

Interface for connection to Wi-Fi MELCloud service

MELCOBEMS MINI (A1M+)

Modbus and BACnet MSTP CN105 adaptor


MELCORETAIL MINI

Retail control and input / output interface


Product Dimensions

MFZ-KT25/35/50VG

Upper View



Front View



Side View

