

MXZ-F R32 Inverter Heat Pump (3.3-12kW)

Multi-Split Units

The **MXZ-F** Multi-Split system allows up to six M Series or Mr Slim wall mounted, cassette, ducted, floor mounted or ceiling suspended indoor units of different capacities to be operated from a single outdoor unit. This makes it an economic and efficient answer for multi-room applications, whilst also offering space saving benefits.

Key Features & Benefits

- Up to six indoor units may be connected to a single outdoor unit
- Energy saving inverter controlled outdoor unit adjusts compressor performance to economically match the demand for heating and cooling
- Units may be added within the capacity of the system as requirements change
- Capacities of indoor units may be mixed to suit individual rooms



MXZ-F - OUTDOOR UNITS		MXZ-2F33VF4	MXZ-2F42VF4	MXZ-2F53VF4	MXZ-3F54VF4	MXZ-3F68VF4	MXZ-4F72VF4	MXZ-4F83VF2	MXZ-5F102VF2	MXZ-6F120VF2
NUMBER OF CONNECTABLE INDOOR UNITS		2	2	2	2-3	2-3	2-4	2-4	2-5	2-6
CAPACITY (kW)	Heating (nominal)	4.0 (1.0-4.1)	4.5 (1.0-4.8)	6.4 (1.1-7.0)	7.0 (2.6-9.0)	8.6 (2.6-10.6)	8.6 (3.4-10.7)	9.3 (3.4-11.6)	10.5 (4.1-14.0)	14.0 (3.5-16.5)
	Cooling (nominal)	3.3 (1.1-3.8)	4.2 (1.1-4.4)	5.3 (1.1-5.6)	5.4 (2.9-6.8)	6.8 (2.9-8.4)	7.2 (3.7-8.8)	8.3 (3.7-9.2)	10.2 (3.9-11.0)	12.0 (3.5-13.5)
	Heating (UK)	3.32 (0.83-3.40)	3.74 (0.84-3.99)	5.38 (0.92 - 5.88)	5.81 (2.16-7.47)	7.14 (2.16-8.80)	7.14 (2.82-8.89)	7.8 (2.82-9.63)	8.7 (3.40-11.63)	11.6 (2.90-13.71)
	Cooling (UK)	3.23 (1.07-3.72)	4.12 (1.08-4.32)	5.30 (1.10-5.60)	5.3 (2.85-6.67)	6.66 (2.84-8.23)	7.0 (3.59-8.56)	8.2 (3.67-9.12)	10.1 (3.86-10.90)	11.9 (3.47-13.39)
COP / EER (nominal)*1		4.40 / 3.90	5.10 / 4.30	4.10 / 3.79	4.60 / 4.10	4.50 / 3.70	4.60 / 3.90	4.65 / 4.21	4.60 / 3.64	4.23 / 3.33
SCOP (ηsh) / SEER (ηsc) (BS EN14825)		4.00 / 6.10	4.60 / 8.69	4.6 / 8.6	4.61 / 8.52	4.12 / 7.96	4.07 / 8.13	4.72 (185.8%) / 8.51 (337.4%)	4.66 (183%) / 8.21 (325.4%)	4.0 (157%) / 6.8 (269%)
ErP ENERGY EFFICIENCY CLASS Heating/Cooling		A+ / A++	A++ / A+++	A++ / A+++	A++ / A+++	A+ / A++	A+ / A++	A++ / A+++	A++ / A++	A+ / A++
MAX AIRFLOW (m³/min)		33.7 / 32.9	33.3 / 27.7	34.7 / 32.7	43.0 / 42.1	43.0 / 42.1	43.0 / 42.1	71 / 55	74 / 62	77 / 63
SOUND PRESSURE LEVEL (dBA)	Heating/Cooling	50 / 49	50 / 44	51 / 46	50 / 46	53 / 48	54 / 48	51 / 49	56 / 52	57 / 55
	Cooling	60	59	61	59	63	63	61	65	69
DIMENSIONS (mm) Width x Depth x Height		800 x 285 x 550	800 x 285 x 550	800 x 285 x 550	840 x 330 x 710	840 x 330 x 710	840 x 330 x 710	950 x 330 x 796	950 x 330 x 796	950 x 330 x 1048
WEIGHT (kg)		33	37	37	58	58	59	62	62	87
ELECTRICAL SUPPLY		220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz
PHASE		Single	Single	Single	Single	Single	Single	Single	Single	Single
POWER INPUT (kW)	Heating/Cooling (nominal)	0.909 / 0.846	0.88 / 0.98	1.56 / 1.40	1.52 / 1.32	1.91 / 1.84	1.87 / 1.85	2.00 / 1.97	2.28 / 2.80	3.31 / 3.60
	Heating/Cooling (UK)	0.82 / 0.68	0.90 / 0.78	1.40 / 1.20	1.38 / 1.06	1.73 / 1.47	1.69 / 1.48	1.80 / 1.57	2.09 / 2.66	3.04 / 3.38
STARTING CURRENT (A)		4.6	4.2	7.6	7.0	10.5	10.0	8.8	12.3	16.1
RUNNING CURRENT (A) Heating/Cooling [MAX]		4.6 / 4.3 [10.0]	4.2 / 4.5 [12.2]	7.1 / 6.2 [10.2]	7.0 / 5.9 [18.0]	10.5 / 9.6 [18.0]	10.0 / 9.5 [18.0]	8.8 / 8.7 [21.4]	10.0 / 12.3 [21.4]	14.5 / 15.7 [29.8]
INTERCONNECTING CABLE No. CORES		4 Core	4 Core	4 Core	4 Core	4 Core	4 Core	4 Core	4 Core	4 Core
TOTAL PIPE LENGTH (m)		20	30	30	50	60	60	70	80	80
MAX PIPE LENGTH PER INDOOR UNIT (m)		15	20	20	25	25	25	25	25	25
MAX HEIGHT DIFFERENCE (m)		10	15 (10 if OU higher than IU)	15 (10 if OU higher than IU)	15 (10 if OU higher than IU)	15 (10 if OU higher than IU)	15 (10 if OU higher than IU)	15	15	15
CHARGE REFRIGERANT (kg) / CO ₂ EQUIVALENT (t) - R32 (GWP 675)		0.8 / 0.54 (20m)	1.0 / 0.68 (30m)	1.0 / 0.68 (30m)	2.4 / 1.62 (50m)	2.4 / 1.62 (60m)	2.4 / 1.62 (60m)	2.4 / 1.62 (70m)	2.4 / 1.62 (80m)	2.4 / 1.62 (80m)
FUSE RATING (BS88) - HRC (A)		16	16	16	25	25	25	25	25	32

Notes: *1 System COP / EER when connected to MSZ-LN / MSZ-AP indoor unit connections.

Combined max running current of all indoors on system must not exceed 3A.

The SEZ-M25DA2 cannot be used when the total indoor capacity is equal to the outdoor capacity, i.e. when the capacity ratio is 1.



