

WY Series (22.4-56kW)

Heat Pump, Water Cooled Condensing Unit



The City Multi **WY** Series Heat Pump VRF system is ideal where a water loop is available and outdoor space is limited. These models utilise water, instead of air, as the energy transfer medium, and benefit from all of the same technology and flexibility as air sourced VRF systems. City Multi WY systems provide the ultimate solution for a breadth of applications requiring heating or cooling at a given time, such as open-plan spaces in offices, call centres and leisure facilities.

Key Features & Benefits

- High efficiency modular systems, with ability to recover energy between units on the water circuit, in either a closed or open loop building, or ground source application
- Benefits from a wide indoor unit range and advanced control options
- Very low impact footprint and service space requirements, ideal for internal location
- Provides continuous heating in winter, without the need for defrost operation

R410A

CONDENSING UNITS		PQHY-P200YLM-A1	PQHY-P250YLM-A1	PQHY-P300YLM-A1	PQHY-P350YLM-A1	PQHY-P400YLM-A1	PQHY-P400YSLM-A1	PQHY-P450YLM-A1	PQHY-P450YSLM-A1	PQHY-P500YLM-A1	PQHY-P500YSLM-A1
CAPACITY (kW)	Heating (nominal max)	25.0	31.5	37.5	45.0	50.0	50.0	56.0	56.0	63.0	63.0
	Cooling (nominal)	22.4	28.0	33.5	40.0	45.0	45.0	50.0	50.0	56.0	56.0
POWER INPUT (kW)	Heating (nominal max)	3.97	5.08	6.25	7.53	8.37	7.94	9.79	6.24	11.43	10.16
	Cooling (nominal)	3.71	4.90	6.04	7.14	8.03	7.70	9.29	5.69	11.17	10.12
OPERATING WATER VOLUME (m³/h)		3.0 ~ 7.2	3.0 ~ 7.2	3.0 ~ 7.2	4.5 ~ 11.6	4.5 ~ 11.6	3.0+3.0~7.2+7.2	4.5 ~ 11.6	3.0+3.0~7.2+7.2	4.5 ~ 11.6	3.0+3.0~7.2+7.2
GUARANTEED OPERATING RANGE (°C) Heating / Cooling		-5~45 / -5~45	-5~45 / -5~45	-5~45 / -5~45	-5~45 / -5~45	-5~45 / -5~45	-5~45 / -5~45	-5~45 / -5~45	-5~45 / -5~45	-5~45 / -5~45	-5~45 / -5~45
COP / EER (nominal max)		6.29 / 6.03	6.20 / 5.71	6.25 / 5.54	5.97 / 5.60	5.97 / 5.60	6.29 / 5.84	5.72 / 5.38	6.24 / 5.69	5.51 / 5.01	6.20 / 5.53
MAX NO. OF CONNECTABLE INDOOR UNITS		17	21	26	30	34	36	39	39	43	43
MAX CONNECTABLE CAPACITY		50 ~ 130%	50 ~ 130%	50 ~ 130%	50 ~ 130%	50 ~ 130%	50 ~ 130%	50 ~ 130%	50 ~ 130%	50 ~ 130%	50 ~ 130%
PIPE SIZE mm (in)	Gas	19.05 (3/4")	22.2 (7/8")	22.2 (7/8")	28.58 (1 1/8")	28.58 (1 1/8")	28.58 (1 1/8")	28.58 (1 1/8")	28.58 (1 1/8")	28.58 (1 1/8")	28.58 (1 1/8")
	Liquid	9.52 (3/8")	9.52 (3/8")**	9.52 (3/8")**	12.7 (1/2")	15.88 (5/8")	15.88 (5/8")	15.88 (5/8")	15.88 (5/8")	15.88 (5/8")	15.88 (5/8")
SOUND PRESSURE LEVEL (dBA)		46	48	54	52	52	49	54	50	54	51
SOUND POWER LEVEL (dBA)		60	62	68	66	66	63	70	64	70.5	65
WEIGHT (kg)		170	170	170	214	214	170 + 170	214	170 + 170	214	170 + 170
DIMENSIONS (mm)	Width	880	880	880	880	880	880 + 880	880	880 + 880	880	880 + 880
	Depth	550	550	550	550	550	550	550	550	550	550
	Height	1100	1100	1100	1450	1450	1100	1450	1100	1450	1100
ELECTRICAL SUPPLY*2		380~415v, 50Hz	380~415v, 50Hz	380~415v, 50Hz	380~415v, 50Hz	380~415v, 50Hz	380~415v, 50Hz	380~415v, 50Hz	380~415v, 50Hz	380~415v, 50Hz	380~415v, 50Hz
PHASE*2		Three	Three	Three	Three	Three	Three	Three	Three	Three	Three
STARTING CURRENT (A)		8	8	8	8	8	8 / 8	8	8 / 8	8	8 / 8
NOMINAL SYSTEM RUNNING CURRENT (A)*2 Heating / Cooling [MAX]		6.3 / 5.9 [16.1]	8.1 / 7.8 [16.1]	10.0 / 9.6 [18.6]	12.0 / 11.4 [23.1]	13.4 / 12.8 [27.6]	12.7 / 12.3 [16.1 + 16.1]	15.7 / 14.8 [32.9]	14.3 / 14.0 [16.1 + 16.1]	18.3 / 17.9 [39.2]	16.2 / 16.2 [16.1 + 16.1]
FUSE RATING (BS88) - HRC (A)*2		1 x 20	1 x 20	1 x 20	1 x 25	1 x 32	1 x 20 / 1 x 20	1 x 40	1 x 20 / 1 x 20	1 x 40	1 x 20 / 1 x 20
MAINS CABLE No. Cores*2		4 + earth	4 + earth	4 + earth	4 + earth	4 + earth	4 + earth	4 + earth	4 + earth	4 + earth	4 + earth
CHARGE REFRIGERANT (kg) / CO ₂ EQUIVALENT (t) R410A (GWP 2088)		5.0 / 10.4	5.0 / 10.4	5.0 / 10.4	6.0 / 12.5	6.0 / 12.5	10.0 / 20.9	6.0 / 12.5	10.0 / 20.9	6.0 / 12.5	10.0 / 20.9
MAX ADDITIONAL REFRIGERANT (kg) / CO ₂ EQUIVALENT (t) R410A (GWP 2088)		21.0 / 43.8	28.0 / 58.5	29.5 / 61.6	41.5 / 86.7	50.0 / 104.4	50.0 / 104.4	51.5 / 107.5	51.5 / 107.5	53.5 / 111.7	53.5 / 111.7


Notes: *SEER/SCOP available separately in the 'City Multi VRF Seasonal Efficiency' document. Based on Ecodesign Lot 21/6 to EN14825 standard. *1 A separate power supply is required for each module. Where more than one figure is quoted there are multiple modules. These products are made to order, please consult your local sales office for delivery schedule.

PIPING RESTRICTIONS	PQHY-P200-500Y(S)LM-A1
TOTAL PIPING LENGTH	300m max for sizes 200-300 / 500m for sizes 350-900
FURTHEST PIPING LENGTH	165m max
FURTHEST PIPING LENGTH AFTER 1ST BRANCH	40m max
BETWEEN INDOOR AND OUTDOOR UNITS - HEIGHT	50m max (40m max if outdoor installed below)
BETWEEN INDOOR AND INDOOR UNITS - HEIGHT	15m max


Product Dimensions

PQHY-P200/250/300YLM-A1


Side View



Front View




Upper View




Product Dimensions

PQHY-P350/400/450/500YLM-A1


Side View



Front View




Upper View




Product Dimensions

PQHY-P400/450/500YSLM-A1

Side View



Front View



WY Series (63-101kW)

Heat Pump, Water Cooled Condensing Unit



The City Multi **WY** Series Heat Pump VRF system is ideal where a water loop is available and outdoor space is limited. These models utilise water, instead of air, as the energy transfer medium, and benefit from all of the same technology and flexibility as air sourced VRF systems. City Multi WY systems provide the ultimate solution for a breadth of applications requiring heating or cooling at a given time, such as open-plan spaces in offices, call centres and leisure facilities.

Key Features & Benefits

- High efficiency modular systems, with ability to recover energy between units on the water circuit, in either a closed or open loop building, or ground source application
- Benefits from a wide indoor unit range and advanced control options
- Very low impact footprint and service space requirements, ideal for internal location
- Provides continuous heating in winter, without the need for defrost operation

R410A

CONDENSING UNITS		PQHY-P550YLM-A1	PQHY-P550YSLM-A1	PQHY-P600YLM-A1	PQHY-P600YSLM-A1	PQHY-P700YSLM-A1	PQHY-P750YSLM-A1	PQHY-P800YSLM-A1	PQHY-P850YSLM-A1	PQHY-P900YSLM-A1
CAPACITY (kW)	Heating (nominal max)	69.0	69.0	76.5	76.5	88.0	95.0	100.0	108.0	113.0
	Cooling (nominal)	63.0	63.0	69.0	69.0	80.0	85.0	90.0	96.0	101.0
POWER INPUT (kW)	Heating (nominal max)	12.27	11.31	14.51	12.75	14.73	15.90	16.75	18.49	19.74
	Cooling (nominal)	12.54	11.55	14.49	12.84	14.73	15.64	16.57	18.03	19.38
OPERATING WATER VOLUME (m³/h)		6.0 ~ 14.4	3.0 + 3.0 ~ 7.2 + 7.2	6.0 ~ 14.4	3.0 + 3.0 ~ 7.2 + 7.2	4.5 + 4.5 ~ 11.6 + 11.6	4.5 + 4.5 ~ 11.6 + 11.6	4.5 + 4.5 ~ 11.6 + 11.6	4.5 + 4.5 ~ 11.6 + 11.6	4.5 + 4.5 ~ 11.6 + 11.6
GUARANTEED OPERATING RANGE (°C) Heating / Cooling		-5~45 / -5~45	-5~45 / -5~45	-5~45 / -5~45	-5~45 / -5~45	-5~45 / -5~45	-5~45 / -5~45	-5~45 / -5~45	-5~45 / -5~45	-5~45 / -5~45
COP / EER (nominal max)		5.62 / 5.02	6.10 / 5.45	5.27 / 4.76	6.00 / 5.37	5.97 / 5.43	5.97 / 5.43	5.97 / 5.43	5.84 / 5.32	5.72 / 5.21
MAX NO. OF CONNECTABLE INDOOR UNITS		47	47	50	50	50	50	50	50	50
MAX CONNECTABLE CAPACITY		50 ~ 130%	50 ~ 130%	50 ~ 130%	50 ~ 130%	50 ~ 130%	50 ~ 130%	50 ~ 130%	50 ~ 130%	50 ~ 130%
PIPE SIZE mm (in)	Gas	28.58 (1 1/8")	28.58 (1 1/8")	28.58 (1 1/8")	28.58 (1 1/8")	34.93 (1 3/8")	34.93 (1 3/8")	34.93 (1 3/8")	41.28 (1 5/8")	41.28 (1 5/8")
	Liquid	15.88 (5/8")	15.88 (5/8")	15.88 (5/8")	15.88 (5/8")	19.05 (3/4")	19.05 (3/4")	19.05 (3/4")	19.05 (3/4")	19.05 (3/4")
SOUND PRESSURE LEVEL (dBA)		56.5	55	56.5	57	55	55	55	56	57
SOUND POWER LEVEL (dBA)		71.5	69	73	71	69	69	69	71.5	73
WEIGHT (kg)		243	170 + 170	243	170 + 170	214 + 214	214 + 214	214 + 214	214 + 214	214 + 214
DIMENSIONS (mm)	Width	880	880 + 880	880	880 + 880	880 + 880	880 + 880	880 + 880	880 + 880	880 + 880
	Depth	550	550	550	550	550	550	550	550	550
	Height	1450	1100	1450	1100	1450	1450	1450	1450	1450
ELECTRICAL SUPPLY*1		380~415v, 50Hz	380~415v, 50Hz	380~415v, 50Hz	380~415v, 50Hz	380~415v, 50Hz	380~415v, 50Hz	380~415v, 50Hz	380~415v, 50Hz	380~415v, 50Hz
PHASE*1		Three	Three	Three	Three	Three	Three	Three	Three	Three
STARTING CURRENT (A)		8	8 / 8	8	8 / 8	8 / 8	8 / 8	8 / 8	8 / 8	8 / 8
NOMINAL SYSTEM RUNNING CURRENT (A)*1 Heating / Cooling [MAX]		19.6 / 20.1 [40.5]	18.1 / 18.5 [18.6 + 16.1]	23.2 / 23.2 [40.5]	20.4 / 20.5 [18.6 + 18.6]	23.6 / 23.6 [23.1 + 23.1]	25.4 / 25.0 [27.6 + 23.1]	26.8 / 26.5 [27.6 + 27.6]	29.6 / 28.9 [32.9 + 27.6]	31.6 / 31.0 [32.9 + 32.9]
FUSE RATING (BS88) - HRC (A)*1		1 x 50	1 x 20 / 1 x 20	1 x 50	1 x 20 / 1 x 20	1 x 25 / 1 x 25	1 x 32 / 1 x 25	1 x 32 / 1 x 32	1 x 40 / 1 x 32	1 x 40 / 1 x 40
MAINS CABLE No. Cores*1		4 + earth	4 + earth	4 + earth	4 + earth	4 + earth	4 + earth	4 + earth	4 + earth	4 + earth
CHARGE REFRIGERANT (kg) / CO ₂ EQUIVALENT (t) R410A (GWP 2088)		11.7 / 24.4	10.0 / 20.9	11.7 / 24.4	10.0 / 20.9	12.0 / 25.1	12.0 / 25.1	12.0 / 25.1	12.0 / 25.1	12.0 / 25.1
MAX ADDITIONAL REFRIGERANT (kg) / CO ₂ EQUIVALENT (t) R410A (GWP 2088)		55.5 / 115.9	54.5 / 113.8	57.0 / 119.0	55.5 / 115.9	65.5 / 136.8	67.5 / 140.9	67.5 / 140.9	70.0 / 146.2	70.0 / 146.2


Notes: *SEER/SCOP available separately in the 'City Multi VRF Seasonal Efficiency' document. Based on Ecodesign Lot 21/6 to EN14825 standard. *1 A separate power supply is required for each module. Where more than one figure is quoted there are multiple modules. These products are made to order, please consult your local sales office for delivery schedule.

PIPING RESTRICTIONS	PQHY-P550-900Y(S)LM-A1
TOTAL PIPING LENGTH	500m max
FURTHEST PIPING LENGTH	165m max
FURTHEST PIPING LENGTH AFTER 1ST BRANCH	40m max
BETWEEN INDOOR AND OUTDOOR UNITS - HEIGHT	50m max (40m max if outdoor installed below)
BETWEEN INDOOR AND INDOOR UNITS - HEIGHT	15m max


Product Dimensions

PQHY-P550/600YLM-A1


Side View



Front View




Upper View




Product Dimensions

PQHY-P550/600YSLM-A1

Side View




Front View



Product Dimensions

PQHY-P700/750/800/850/900YSLM-A1

Side View



Front View

