

PEFY-WP-VMA-E

Ceiling Concealed Ducted Indoor Unit

The **PEFY-WP-VMA-E** low-height ducted indoor unit is concealed within the ceiling space and connects to the Hybrid Branch Controller, using water as the heat transfer medium. Offering unobtrusive air conditioning, the flexibility of duct layout allows airflow patterns to be arranged to suit any application.

Key Features & Benefits

- Low height allowing installation in smaller spaces - only 250mm
- Centrifugal fan minimises noise levels to as low as 23dBA (sizes 20-25) for minimal disturbance
- Wide range of external static pressure settings across entire range (35-150Pa) offers flexibility of application
- Drain pump included as standard
- CN105 connector available - connect to MELCOBEMS MINI for simple BEMS interfacing
- No refrigerant in occupied spaces, removing the need for leak detection under BS EN378
- Higher air off temperatures than standard VRF, allowing for improved comfort levels
- Compatible with Plasma Quad Connect - an innovative, bolt-on air purifying device which neutralises viruses, bacteria, allergens, PM2.5, mould and dust. For more information, please refer to page 1.1.7




INDOOR UNITS		PEFY-WP20VMA-E	PEFY-WP25VMA-E	PEFY-WP32VMA-E	PEFY-WP40VMA-E	PEFY-WP50VMA-E	PEFY-WP63VMA-E	PEFY-WP80VMA-E
CAPACITY (kW)	Heating (nominal)	2.5	3.2	4.0	5.0	6.3	8.0	10.0
	Cooling (nominal)	2.2	2.8	3.6	4.5	5.6	7.1	9.0
	UK Heating	2.5	3.2	4.0	5.0	6.3	8.0	10.0
	UK Total Cooling - Hi (Sensible)	2.00 (1.80)	2.50 (2.50)	3.20 (3.00)	4.00 (3.80)	5.00 (4.20)	6.40 (5.10)	8.10 (7.20)
	UK Total Cooling - Mi	1.92	2.40	3.07	3.84	4.80	6.15	7.76
POWER INPUT (kW)	UK Total Cooling - Lo	1.79	2.24	2.85	3.53	4.41	5.64	7.17
	Heating (nominal)	0.05	0.07	0.9	0.12	0.12	0.12	0.22
	Cooling (nominal)	0.07	0.09	0.11	0.14	0.14	0.14	0.24
AIRFLOW (l/s)		Lo-Mi-Hi	125-150-175	167-200-233	200-242-283	242-300-350	242-300-350	383-467-550
EXTERNAL STATIC PRESSURE (Pa)		35-50-70-100-150	35-50-70-100-150	35-50-70-100-150	35-50-70-100-150	35-50-70-100-150	35-50-70-100-150	35-50-70-100-150
SOUND PRESSURE LEVEL (dBA) (50Pa) Lo-Mi-Hi		23-26-29	23-27-30	25-29-32	26-29-34	26-29-34	26-29-34	28-33-37
WEIGHT (kg)		21	26	26	31	31	31	40
DIMENSIONS (mm)	Width	700	900	900	1100	1100	1100	1400
	Depth	732	732	732	732	732	732	732
	Height	250	250	250	250	250	250	250
ELECTRICAL SUPPLY		220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz
PHASE		Single	Single	Single	Single	Single	Single	Single
RUNNING CURRENT (A) Heating / Cooling		0.44 / 0.55	0.53 / 0.64	0.63 / 0.74	1.04 / 1.15	1.04 / 1.15	1.04 / 1.15	1.36 / 1.47
FUSE RATING (BS88) - HRC (A)		6	6	6	6	6	6	6
MAINS CABLE No. Cores		3	3	3	3	3	3	3
WATER PIPE CONNECTION		3/4" BSP SCREW	3/4" BSP SCREW	3/4" BSP SCREW	3/4" BSP SCREW	3/4" BSP SCREW	1 1/4" BSP SCREW	1 1/4" BSP SCREW

Note: HVRF indoor units can only be configured with the CMB-WM HBC (HVRF) and PURY-(E)M YNW-A1 or PQRY-P YLM-A1 outdoor units.


Product Dimensions

PEFY-WP20/25/32/40/50VMA-E

Upper View




Front View



Model	A	B	C	D	E	F	G	①Water pipe (From HBC unit)	②Water pipe (To HBC unit)
PEFY-WP20VMA-E	700	754	800	660	7	600	658	Rc3/4 screw	
PEFY-WP25.32VMA-E	900	954	1000	860	9	800	858		
PEFY-WP40.50VMA-E	1100	1154	1200	1060	11	1000	1058		


Side View




Product Dimensions

PEFY-WP63/80VMA-E

Upper View



Front View



Model	A	B	C	D	E	F	G	① Water pipe (From HBC unit)	② Water pipe (To HBC unit)
PEFY-WP63VMA-E	1100	1154	1200	1060	11	1000	1058	Rc1-1/4 screw	
PEFY-WP80VMA-E	1400	1454	1500	1360	14	1300	1358		

Side View

