

R2 Series HVRF High Efficiency (22.4-56kW)

Simultaneous Heating and
Cooling with Heat Recovery
Outdoor Unit

Delivering outstanding Seasonal Energy Efficiency, the award-winning City Multi R2 Series HVRF High Efficiency system provides simultaneous heating and cooling, with the added benefit of heat recovery. By utilising lower GWP R32 refrigerant, the **PURY-EM** helps businesses achieve their Corporate Social Responsibility targets, as well as future-proof their buildings and equipment.

Key Features & Benefits

- High efficiency system delivers outstanding seasonal energy performance
- Heat recovery achieves energy savings of up to 30% over heat pump systems
- Adjustable noise level options to suit application
- No refrigerant in occupied spaces, removing the need for leak detection under BS EN378
- Decentralised system allows for phased installation - ideal for Cat A to Cat B fit-outs

R32



OUTDOOR UNITS		PURY-EM200YNW-A1	PURY-EM250YNW-A1	PURY-EM300YNW-A1	PURY-EM300YNW-A1 X 2HBC	PURY-EM350YNW-A1	PURY-EM350YNW-A1 X 2HBC	PURY-EM400YNW-A1	PURY-EM450YNW-A1	PURY-EM500YNW-A1
CAPACITY (kW)	Heating (nominal max)	25.0	31.5	37.5	37.5	45.0	45.0	50.0	56.0	63.0
	Cooling (nominal)	22.4	28.0	33.5	33.5	40.0	40.0	45.0	50.0	56.0
	High Performance Heating (UK)	25.0	31.5	37.5	37.5	42.8	42.8	47.5	50.4	58.0
	COP Priority Heating (UK)	22.8	28.7	32.3	32.3	38.7	38.7	43.0	49.3	54.8
	Cooling (UK)	20.1	25.1	30.0	30.0	35.8	35.8	40.3	44.8	50.1
POWER INPUT (kW)	Heating (nominal max)	6.23	8.84	10.46	9.93	13.10	12.16	13.88	15.77	17.45
	Cooling (nominal)	5.13	7.69	10.03	8.52	13.91	11.33	13.84	15.24	18.06
	High Performance Heating (UK)	7.54	10.70	14.33	13.60	17.95	16.66	16.10	18.29	20.24
	COP Priority Heating (UK)	6.23	8.84	10.46	9.93	13.10	12.16	13.46	15.30	16.93
	Cooling (UK)	2.98	4.46	5.82	4.94	8.07	6.57	8.87	9.77	11.58
COP / EER (nominal max)		4.01 / 4.36	3.56 / 3.64	3.58 / 3.33	3.77 / 3.93	3.43 / 2.87	3.70 / 3.53	3.60 / 3.25	3.55 / 3.28	3.61 / 3.10
MAX No. OF CONNECTABLE INDOOR UNITS		30	37	45	45	35	35	40	45	50
MAX CONNECTABLE CAPACITY		50-150% OU Capacity	50-150% OU Capacity	50-150% OU Capacity	50-150% OU Capacity	50-150% OU Capacity	50-150% OU Capacity	50-150% OU Capacity	50-150% OU Capacity	50-150% OU Capacity
AIRFLOW (m³/min)	High	170	185	240	240	250	250	315	315	295
	Liquid	19.05 (3/4")	22.2 (7/8")	22.2 (7/8")	22.2 (7/8")	28.58 (1-1/8")	28.58 (1-1/8")	28.58 (1-1/8")	28.58 (1-1/8")	28.58 (1-1/8")
PIPE SIZE mm (in)	Gas	19.05 (3/4")	22.2 (7/8")	22.2 (7/8")	22.2 (7/8")	28.58 (1-1/8")	28.58 (1-1/8")	28.58 (1-1/8")	28.58 (1-1/8")	28.58 (1-1/8")
	Liquid	15.88 (5/8")	15.88 (5/8")	15.88 (5/8")	15.88 (5/8")	15.88 (5/8")	15.88 (5/8")	19.05 (3/4")	19.05 (3/4")	19.05 (3/4")
SOUND PRESSURE LEVEL (dBA) Heating / Cooling		59.0 / 59.0	61.0 / 60.5	67.0 / 61.0	67.0 / 61.0	64.0 / 62.5	64.0 / 62.5	69.0 / 65.0	70.0 / 65.5	64.5 / 63.5
SOUND POWER LEVEL (dBA) Heating / Cooling		78.0 / 76.0	80.0 / 78.5	86.5 / 80.0	86.5 / 80.0	83.0 / 81.0	83.0 / 81.0	88.0 / 83.0	89.0 / 83.0	84.0 / 82.0
WEIGHT (kg)		231	231	231	231	276	276	280	305	348
DIMENSIONS (mm)	Width	920	920	920	920	1240	1240	1240	1240	1750
	Depth	740	740	740	740	740	740	740	740	740
	(1798mm without legs) Height	1858	1858	1858	1858	1858	1858	1858	1858	1858
ELECTRICAL SUPPLY ^{*1}		380-415v, 50Hz	380-415v, 50Hz	380-415v, 50Hz	380-415v, 50Hz	380-415v, 50Hz	380-415v, 50Hz	380-415v, 50Hz	380-415v, 50Hz	380-415v, 50Hz
PHASE ^{*1}		Three	Three	Three	Three	Three	Three	Three	Three	Three
STARTING CURRENT (A) ^{*1}		8	8	8	8	8	8	8	8	8
NOMINAL SYSTEM RUNNING CURRENT (A) ^{*1} Heating/Cooling [MAX]		9.9 / 8.2 [16.1]	14.1 / 12.3 [21.8]	16.7 / 16.0 [23.9]	15.9 / 13.6 [23.9]	21.0 / 22.3 [30.0]	19.5 / 18.1 [30.0]	22.2 / 22.1 [35.9]	25.2 / 24.4 [36.9]	27.9 / 28.9 [46.9]
GUARANTEED OPERATING RANGE (°C) Heating / Cooling		-20~-15.5 / -5~-52	-20~-15.5 / -5~-52	-20~-15.5 / -5~-52	-20~-15.5 / -5~-52	-20~-15.5 / -5~-52	-20~-15.5 / -5~-52	-20~-15.5 / -5~-52	-20~-15.5 / -5~-52	-20~-15.5 / -5~-52
FUSE RATING (MCB sizes BS EN 60947-2) - (A) ^{*1}		1 x 20	1 x 25	1 x 25	1 x 25	1 x 32	1 x 32	1 x 40	1 x 40	1 x 50
MAINS CABLE No. Cores ^{*1}		4	4	4	4	4	4	4	4	4
CHARGE REFRIGERANT (kg) / CO ₂ EQUIVALENT (t) R32 (GWP 675)		5.2 / 3.5	5.2 / 3.5	5.2 / 3.5	5.2 / 3.5	8 / 5.4	8 / 5.4	8 / 5.4	10.8 / 7.3	10.8 / 7.3
MAX ADDITIONAL REFRIGERANT (kg) / CO ₂ EQUIVALENT (t) R32 (GWP 675)		13.5 / 9.1	13.5 / 9.1	15.5 / 10.5	15.5 / 10.5	15.5 / 10.5	15.5 / 10.5	19.5 / 13.2	19.5 / 13.2	19.5 / 13.2

Notes: *SEER/SCOP available separately in the 'City Multi HVRF Seasonal Efficiency' document. Based on Ecodesign Lot 21/6 to EN14825 standard.

Nominal Conditions: Cooling: indoor 27°C DB, 19°C WB; outdoor 35°C DB, 24°C WB. Nominal Max Conditions: Heating: indoor 20°C DB; outdoor 7°C DB, 6°C WB.

UK Conditions: Cooling: indoor 21°C DB, 15°C WB; outdoor 27°C DB, UK Conditions: Heating: indoor 20°C DB, outdoor 0°C DB, -1°C WB.


*1 A separate power supply is required for each module. Where more than one figure is quoted there are multiple modules. Specification subject to change.

R410A equivalent systems are also available - please contact your local sales office for further information.

R32 | HybridVRF


Product Dimensions

PURY-EM200/250/300YNW-A1




Product Dimensions

PURY-EM350/400/450YNW-A1



Product Dimensions

PURY-EM500YNW-A1



R2 Series HVRF Standard Efficiency (22.4-56kW)

Simultaneous Heating and Cooling with Heat Recovery Outdoor Unit

The award-winning City Multi R2 Series HVRF Heat Recovery system meets the demand for simultaneous heating and cooling, with the added benefit of heat recovery. By utilising lower GWP R32 refrigerant, the **PURY-M** helps businesses achieve their Corporate Social Responsibility targets, as well as future-proof their buildings and equipment.

Key Features & Benefits

- Heat recovery achieves energy savings of up to 30% over heat pump systems
- Provides simultaneous heating and cooling with a high level of thermal comfort
- Adjustable noise level options to suit application
- No refrigerant in occupied spaces, removing the need for leak detection under BS EN378
- Decentralised system allows for phased installation - ideal for Cat A to Cat B fit-outs

R32


OUTDOOR UNITS		PURY-M200YNW-A1	PURY-M250YNW-A1	PURY-M300YNW-A1	PURY-M300YNW-A1 X 2HBC	PURY-M350YNW-A1	PURY-M350YNW-A1 X 2HBC	PURY-M400YNW-A1	PURY-M450YNW-A1	PURY-M500YNW-A1
CAPACITY (kW)	Heating (nominal max)	25.0	31.5	37.5	37.5	45.0	45.0	45.0	56.0	63.0
	Cooling (nominal)	22.4	28.0	33.5	33.5	40.0	40.0	45.0	50.0	56.0
	High Performance Heating (UK)	25.0	31.5	37.5	37.5	42.8	42.8	42.8	50.4	58.0
	COP Priority Heating (UK)	22.8	28.7	32.3	32.3	38.7	38.7	38.7	49.3	54.8
	Cooling (UK)	20.1	25.1	30.0	30.0	35.8	35.8	40.3	44.8	50.1
POWER INPUT (kW)	Heating (nominal max)	6.39	9.15	11.00	10.33	13.14	12.16	14.08	16.18	18.26
	Cooling (nominal)	5.53	8.40	11.65	9.88	14.93	12.15	15.15	15.47	22.25
	High Performance Heating (UK)	7.73	11.07	15.07	14.15	18.00	16.66	16.33	18.77	21.18
	COP Priority Heating (UK)	6.39	9.15	11.00	10.33	13.14	12.16	13.66	15.69	17.71
	Cooling (UK)	3.21	4.87	6.76	5.73	8.66	7.05	9.71	9.92	14.26
COP / EER (nominal max)		3.91 / 4.05	3.44 / 3.33	3.40 / 2.87	3.63 / 3.39	3.42 / 2.67	3.70 / 3.29	3.55 / 2.97	3.46 / 3.23	3.45 / 2.51
MAX No. OF CONNECTABLE INDOOR UNITS		30	37	45	45	35	35	40	45	50
MAX CONNECTABLE CAPACITY		50~150% OU Capacity	50~150% OU Capacity	50~150% OU Capacity	50~150% OU Capacity	50~150% OU Capacity	50~150% OU Capacity	50~150% OU Capacity	50~150% OU Capacity	50~150% OU Capacity
AIRFLOW (m³/min)	High	170	185	240	240	250	250	315	315	295
	Gas	19.05 (3/4")	22.2 (7/8")	22.2 (7/8")	22.2 (7/8")	28.58 (1-1/8")	28.58 (1-1/8")	28.58 (1-1/8")	28.58 (1-1/8")	28.58 (1-1/8")
PIPE SIZE mm (in)	Liquid	15.88 (5/8")	15.88 (5/8")	15.88 (5/8")	15.88 (5/8")	15.88 (5/8")	15.88 (5/8")	19.05 (3/4")	19.05 (3/4")	19.05 (3/4")
SOUND PRESSURE LEVEL (dBA)	Heating / Cooling	59.0 / 59.0	61.0 / 60.5	67.0 / 61.0	67.0 / 61.0	64.0 / 62.5	64.0 / 62.5	69.0 / 65.0	70.0 / 65.5	64.5 / 63.5
SOUND POWER LEVEL (dBA)	Heating / Cooling	78.0 / 76.0	80.0 / 78.5	86.5 / 80.0	86.5 / 80.0	83.0 / 81.0	83.0 / 81.0	88.0 / 83.0	89.0 / 83.0	84.0 / 82.0
WEIGHT (kg)		227	227	227	227	270	270	273	293	337
DIMENSIONS (mm)	Width	920	920	920	920	1240	1240	1240	1240	1750
	Depth	740	740	740	740	740	740	740	740	740
	Height	1858	1858	1858	1858	1858	1858	1858	1858	1858
(1798mm without legs)										
ELECTRICAL SUPPLY*1		380~415v, 50Hz	380~415v, 50Hz	380~415v, 50Hz	380~415v, 50Hz	380~415v, 50Hz	380~415v, 50Hz	380~415v, 50Hz	380~415v, 50Hz	380~415v, 50Hz
PHASE*1		Three	Three	Three	Three	Three	Three	Three	Three	Three
STARTING CURRENT (A)*1		8	8	8	8	8	8	8	8	8
NOMINAL SYSTEM RUNNING CURRENT (A)*1 Heating/Cooling [MAX]		10.2 / 8.8 [16.1]	14.6 / 13.4 [22.5]	17.6 / 18.6 [25.6]	16.5 / 15.8 [25.6]	21.0 / 23.9 [31.6]	19.5 / 19.4 [31.6]	22.5 / 24.2 [39.3]	25.9 / 24.8 [40.2]	29.2 / 35.6 [56.6]
GUARANTEED OPERATING RANGE (°C) Heating / Cooling		-20~15.5 / -5~52	-20~15.5 / -5~52	-20~15.5 / -5~52	-20~15.5 / -5~52	-20~15.5 / -5~52	-20~15.5 / -5~52	-20~15.5 / -5~52	-20~15.5 / -5~52	-20~15.5 / -5~52
FUSE RATING (MCB sizes BS EN 60947-2) - (A)*1		1 x 20	1 x 25	1 x 32	1 x 32	1 x 32	1 x 32	1 x 40	1 x 50	1 x 63
MAINS CABLE No. Cores*1		4	4	4	4	4	4	4	4	4
CHARGE REFRIGERANT (kg) / CO ₂ EQUIVALENT (t) R32 (GWP 675)		5.2 / 3.5	5.2 / 3.5	5.2 / 3.5	5.2 / 3.5	8 / 5.4	8 / 5.4	8 / 5.4	10.8 / 7.3	10.8 / 7.3
MAX ADDITIONAL REFRIGERANT (kg) / CO ₂ EQUIVALENT (t) R32 (GWP 675)		13.5 / 9.1	13.5 / 9.1	15.5 / 10.5	15.5 / 10.5	15.5 / 10.5	15.5 / 10.5	19.5 / 13.2	19.5 / 13.2	19.5 / 13.2

Notes: *SEER/SCOP available separately in the 'City Multi HVRF Seasonal Efficiency' document. Based on Ecodesign Lot 21/6 to EN14825 standard.
Nominal Conditions: Cooling: indoor 27°C DB, 19°C WB; outdoor 35°C DB, 24°C WB. Nominal Max Conditions: Heating: indoor 20°C DB; outdoor 7°C DB, 6°C WB.
UK Conditions: Cooling: indoor 21°C DB, 15°C WB; outdoor 27°C DB. UK Conditions: Heating: indoor 20°C DB, outdoor 0°C DB, -1°C WB.
*1 A separate power supply is required for each module. Where more than one figure is quoted there are multiple modules. Specification subject to change.
R410A equivalent systems are also available - please contact your local sales office for further information.

R32 | HybridVRF


Product Dimensions

PURY-M200/250/300YNW-A1



Product Dimensions

PURY-M350/400/450YNW-A1



Product Dimensions

PURY-M500YNW-A1

