PEAD-M R32 Ceiling Concealed Ducted System

Power Inverter Heat Pump
(Three Phase)







POWER INVERTER

The **PEAD-M Power Inverter** range is a ceiling concealed ducted system that blends a host of outstanding features with an unobtrusive design (only 250mm height) for easy installation and maintenance. Offering high seasonal efficiency, advanced control options and extended pipe runs, the units also come with a wide range of external static pressure settings, making this range an extremely flexible solution for applications such as light commercial, schools and warehousing.

Key Features & Benefits

- Increased comfort levels through advanced airflow and smart defrost features
- 100m pipe run, increasing application capability
- PAR-42MAAB controller allows effective energy monitoring
- Improved efficiency through new fan motor
- Full heating capacity down to -3°C
- Drain pump included as standard
- Compatible with Plasma Quad Connect - an innovative, bolt-on air purifying device which neutralises viruses, bacteria, allergens, PM2.5, mould and dust. For more information, please refer to page 1.1.7

R32

PEAD-M - INDOOR UNITS		PEAD-M100JA3	PEAD-M125JA3	PEAD-M140JA3
CAPACITY (kW)	Heating (nominal)	11.2 (2.7-14.0)	14.0 (3.2-16.0)	16.0 (3.7-18.0)
	Cooling (nominal)	9.5 (4.9-11.4)	12.5 (5.1-14.0)	13.4 (5.4-15.0)
	Heating (UK)	8.06 (1.94-10.08)	10.08 (2.30-11.52)	11.52 (2.66-12.96)
	Cooling (UK)	8.74 (4.51-10.49)	11.50 (4.69-12.88)	12.33 (4.97-13.80)
SHF (nominal)		0.82	0.78	0.77
COP / EER (nominal)		4.40 / 4.20	3.72 / 3.70	3.90 / 3.62
SCOP (ηsh) / SEER (ηsc) (BS EN14825)		4.40 / 6.50	4.18 (164.4%) / 6.68 (264.4%)	4.15 (163.1%) / 6.50 (256.8%)
ERP ENERGY EFFICIENCY CLASS	Heating/Cooling	A+ / A++	-	-
AIRFLOW (l/s)	Lo-Mi-Hi	383-467-533	467-567-617	492-592-667
PIPE SIZE MM (in)	Gas	15.88 (5/8")	15.88 (5/8")	15.88 (5/8")
	Liquid	9.52 (3/8")	9.52 (3/8")	9.52 (3/8")
EXTERNAL STATIC PRESSURE (Pa)		35-50-70-100-150	35-50-70-100-150	35-50-70-100-150
SOUND PRESSURE LEVEL (dBA)	Lo-Mi-Hi	31-36-39	35-39-41	34-38-41
SOUND POWER LEVEL (dBA)		63	66	66
DIMENSIONS (mm)	Width x Depth x Height	1400 x 732 x 250	1400 x 732 x 250	1600 x 732 x 250
WEIGHT (kg)		37	38	42
ELECTRICAL SUPPLY		Fed by Outdoor Unit	Fed by Outdoor Unit	Fed by Outdoor Unit
FUSE RATING (BS88) - HRC (A)		6	6	6
INTERCONNECTING CABLE NO. CORES		4	4	4
WIRED REMOTE CONTROLLER REFERENCE		PAR-42MAAB	PAR-42MAAB	PAR-42MAAB

PUZ-ZM - OUTDOOR UNITS		PUZ-ZM100YDA2 [3]	PUZ-ZM125YDA2 [3]	PUZ-ZM140YDA2 [3]
SOUND PRESSURE LEVEL (dBA)	Heating/Cooling	48 / 44	50 / 47	51 / 49
SOUND POWER LEVEL (dBA)	Cooling	63	66	68
WEIGHT (kg)		114	116	121
DIMENSIONS (mm)	Width x Depth x Height	1100 x 460+45 x 870	1100 x 460+45 x 870	1100 x 460+45 x 870
ELECTRICAL SUPPLY		380-415v,50Hz	380-415v,50Hz	380-415v,50Hz
PHASE		Three	Three	Three
SYSTEM POWER INPUT (kW)	Heating/Cooling (nominal)	2.546 / 2.262	3.764 / 3.379	4.103 / 3.702
	Heating/Cooling (UK)	2.09 / 1.92	3.09 / 2.87	3.36 / 3.15
STARTING CURRENT (A)		3.5	3.5	3.5
SYSTEM RUNNING CURRENT (A)	Heating/Cooling [MAX]	3.91 / 3.47 [10.3]	5.78 / 5.19 [11.3]	6.30 / 5.68 [11.6]
FUSE RATING (BS88) - HRC (A)		16	16	16
MAINS CABLE NO. CORES		5	5	5
MAX PIPE LENGTH (m)		100	100	100
MAX HEIGHT DIFFERENCE (m)		30	30	30
CHARGE REFRIGERANT (kg) / CO_2 EQUIVALENT (t)	R32 (GWP 675) - 40m	3.60 / 2.43	3.60 / 2.43	3.60 / 2.43
MAX ADDITIONAL REFRIGERANT (kg) / CO_2 EQUIVALENT (t)	R32 (GWP 675)	2.40 / 1.62	2.40 / 1.62	2.40 / 1.62

[3] Three Phase

Accessories

Indoor Units

MAC-100FT-E

Plasma Quad Connect air purifying device

PAC-HA31PAR

Plasma Quad Connect metal fitment

Outdoor Units

PAC-SL12SG-E

Air outlet guide for PUZ-ZM100-140YDA2

System Control Units

PAC-SA89TA

Remote on/off adaptor (3 wire adaptor)

PAC-SA88HA

Run/fault adaptor (5 wire adaptor)

PAC-SE42TS-E

Remote sensor

PAR-CT01MAA-SB/PB

Touch screen wired remote controller (PB=Premium Finish)

PAR-42MAAB/MAAPB

Standard wired remote controller (MAAPB = Black Finish)

MAC-597IF-E

Interface for Wi-Fi connection to MELCloud Home service

MELCOBEMS MINI (A1M+)

Modbus and BACnet MSTP CN105 adaptor

MELCORETAIL MINI

Retail control and input / output interface


PAC-SL16MA-E

M-NET adaptor for size 100 to 140


Note: Please see page 1.3.66 for the full range of accessories.

Product Dimensions PEAD-M100/125/140JA3


Front View



Upper View



Side View



Model	A	B	C	D	E	F
PEAD-M100,125JA3	1400	1454	1500	1360	14	1300
PEAD-M140JA3	1600	1654	1700	1560	16	1500