



# MULTI-SPLIT SYSTEM

## INDOOR UNITS SPECIFICATION FOR MULTI COMBINATIONS

Wall Mounted

### SRK-ZSX



| Item                        |                       | Model  | SRK20ZSX-WF*,-W                                                        | SRK25ZSX-WF*,-W         | SRK35ZSX-WF*,-W         | SRK50ZSX-WF*,-W         | SRK60ZSX-WF*,-W          |
|-----------------------------|-----------------------|--------|------------------------------------------------------------------------|-------------------------|-------------------------|-------------------------|--------------------------|
| Nominal cooling capacity    |                       | kW     | 2.0                                                                    | 2.5                     | 3.5                     | 5.0                     | 6.0                      |
| Nominal heating capacity    |                       | kW     | 3.0                                                                    | 3.4                     | 4.5                     | 5.8                     | 6.8                      |
| Sound power level           | Cooling               | dB(A)  | 53                                                                     | 55                      | 58                      | 59                      | 62                       |
|                             | Heating               | dB(A)  | 55                                                                     | 56                      | 58                      | 62                      | 63                       |
| Sound pressure level        | Cooling(Hi/Me/Lo/Ulo) | dB(A)  | 38 / 31 / 24 / 19                                                      | 39 / 33 / 25 / 19       | 43 / 35 / 26 / 19       | 44 / 39 / 31 / 22       | 48 / 41 / 33 / 22        |
|                             | Heating(Hi/Me/Lo/Ulo) | dB(A)  | 38 / 33 / 25 / 19                                                      | 40 / 34 / 27 / 19       | 42 / 35 / 28 / 19       | 47 / 41 / 33 / 23       | 47 / 42 / 34 / 23        |
| Air flow                    | Cooling(Hi/Me/Lo/Ulo) | m³/min | 11.3 / 9.1 / 6.0 / 5.0                                                 | 12.2 / 10.0 / 6.7 / 5.0 | 13.1 / 10.8 / 7.3 / 5.0 | 14.3 / 12.4 / 7.8 / 5.4 | 16.3 / 13.4 / 8.9 / 5.4  |
|                             | Heating(Hi/Me/Lo/Ulo) |        | 12.2 / 10.3 / 7.2 / 5.4                                                | 12.8 / 11.0 / 7.8 / 5.4 | 13.9 / 11.8 / 8.6 / 5.4 | 17.3 / 14.3 / 9.8 / 6.2 | 17.8 / 13.7 / 10.9 / 6.2 |
| Exterior dimensions (H×W×D) |                       | mm     | 305×920×220                                                            |                         |                         |                         |                          |
| Net weight                  |                       | kg     | 13.0                                                                   |                         |                         |                         |                          |
| Refrigerant piping size     | Liquid / Gas          | Φmm    | 6.35(1/4") / 9.52(3/8")                                                |                         |                         |                         | 6.35(1/4") / 12.7(1/2")  |
| Clean filter                |                       |        | Allergen Clear Filter ×1, Photocatalytic Washable Deodorising Filter×1 |                         |                         |                         |                          |

\* Colour variation available [-WFB] [-WFT]

Wall Mounted

### SRK-ZR



| Item                        | Model                 | SRK71ZR-WF, -W                                                         | SRK80ZR-WF, -W             |
|-----------------------------|-----------------------|------------------------------------------------------------------------|----------------------------|
| Nominal cooling capacity    | kW                    | 7.1                                                                    | 8.0                        |
| Nominal heating capacity    | kW                    | 8.0                                                                    | 9.0                        |
| Sound power level           | Cooling               | dB(A)                                                                  | 57                         |
|                             | Heating               | dB(A)                                                                  | 60                         |
| Sound pressure level        | Cooling(Hi/Me/Lo/Ulo) | dB(A)                                                                  | 44 / 41 / 37 / 25          |
|                             | Heating(Hi/Me/Lo/Ulo) | dB(A)                                                                  | 46 / 39 / 35 / 28          |
| Air flow                    | Cooling(Hi/Me/Lo/Ulo) | m <sup>3</sup> /min                                                    | 20.5 / 18.6 / 16.2 / 10.4  |
|                             | Heating(Hi/Me/Lo/Ulo) | m <sup>3</sup> /min                                                    | 25.0 / 19.8 / 17.3 / 13.3  |
| Exterior dimensions (H×W×D) | mm                    | 339×1197×262                                                           |                            |
| Net weight                  | kg                    | 15.5                                                                   | 16.5                       |
| Refrigerant piping size     | Liquid / Gas          | Φmm                                                                    | 6.35 (1/4") / 15.88 (5/8") |
| Clean filter                |                       | Allergen Clear Filter ×1, Photocatalytic Washable Deodorising Filter×1 |                            |

Wall Mounted

### SRK-ZS

New!



| Item                        |                       | Model  | SRK15ZS-WF*                                                             | SRK20ZS-WF*, -W        | SRK25ZS-WF*, -W        | SRK35ZS-WF*, -W         | SRK50ZS-WF*, -W         |                         |
|-----------------------------|-----------------------|--------|-------------------------------------------------------------------------|------------------------|------------------------|-------------------------|-------------------------|-------------------------|
| Nominal cooling capacity    |                       | kW     | 1.5                                                                     | 2.0                    | 2.5                    | 3.5                     | 5.0                     |                         |
| Nominal heating capacity    |                       | kW     | 2.0                                                                     | 3.0                    | 3.4                    | 4.5                     | 5.8                     |                         |
| Sound power level           | Cooling               | dB(A)  | 48                                                                      | 48                     | 50                     | 54                      | 59                      |                         |
|                             | Heating               | dB(A)  | 50                                                                      | 50                     | 53                     | 56                      | 60                      |                         |
| Sound pressure level        | Cooling(Hi/Me/Lo/Ulo) | dB(A)  | 34 / 25 / 22 / 19                                                       | 34 / 25 / 22 / 19      | 36 / 28 / 23 / 19      | 40 / 30 / 26 / 19       | 46 / 36 / 29 / 22       |                         |
|                             | Heating(Hi/Me/Lo/Ulo) | dB(A)  | 36 / 29 / 23 / 19                                                       | 36 / 29 / 23 / 19      | 39 / 30 / 24 / 19      | 41 / 36 / 25 / 19       | 46 / 37 / 31 / 24       |                         |
| Air flow                    | Cooling(Hi/Me/Lo/Ulo) | m³/min | 9.3 / 7.0 / 5.9 / 5.0                                                   | 9.3 / 7.0 / 5.9 / 5.0  | 9.9 / 8.0 / 5.9 / 5.0  | 11.3 / 8.7 / 7.0 / 5.0  | 12.1 / 9.9 / 7.4 / 5.9  |                         |
|                             | Heating(Hi/Me/Lo/Ulo) |        | 10.0 / 8.5 / 6.5 / 5.9                                                  | 10.0 / 8.5 / 6.5 / 5.9 | 11.3 / 8.7 / 6.7 / 5.9 | 12.3 / 11.0 / 7.0 / 5.6 | 13.9 / 11.2 / 9.1 / 7.4 |                         |
| Exterior dimensions (H×W×D) |                       | mm     | 290×870×230                                                             |                        |                        |                         |                         |                         |
| Net weight                  |                       | kg     | 9.5                                                                     |                        |                        |                         |                         | 10.0                    |
| Refrigerant piping size     | Liquid / Gas          | Φmm    | 6.35(1/4") / 9.52(3/8")                                                 |                        |                        |                         |                         | 6.35(1/4") / 12.7(1/2") |
| Clean filter                |                       |        | Allergen Clear Filter ×1, Photocatalytic Washable Deodorising Filter ×1 |                        |                        |                         |                         |                         |

\* Colour variation available [-WFB] [-WFT]

Wall Mounted

### SKM-ZSP

• Compact and Light weight

New!



| Item                        |                       | Model  | SKM15ZSP-W              | SKM20ZSP-W      | SKM25ZSP-W      | SKM35ZSP-W      |
|-----------------------------|-----------------------|--------|-------------------------|-----------------|-----------------|-----------------|
| Nominal cooling capacity    |                       | kW     | 1.5                     | 2.0             | 2.5             | 3.5             |
| Nominal heating capacity    |                       | kW     | 2.0                     | 3.0             | 3.4             | 4.5             |
| Sound power level           | Cooling               | dB(A)  | 57                      | 57              | 57              | 58              |
|                             | Heating               | dB(A)  | 56                      | 56              | 56              | 58              |
| Sound pressure level        | Cooling(Hi/Me/Lo/Ulo) | dB(A)  | 42 / 35 / 22            | 42 / 35 / 22    | 43 / 36 / 23    | 44 / 37 / 25    |
|                             | Heating(Hi/Me/Lo/Ulo) | dB(A)  | 41 / 36 / 26            | 41 / 36 / 26    | 41 / 36 / 27    | 42 / 37 / 30    |
| Air flow                    | Cooling(Hi/Me/Lo/Ulo) | m³/min | 8.5 / 7.0 / 5.0         | 8.5 / 7.0 / 5.0 | 8.5 / 7.0 / 5.0 | 9.0 / 7.5 / 5.0 |
|                             | Heating(Hi/Me/Lo/Ulo) |        | 8.0 / 7.0 / 5.5         | 8.0 / 7.0 / 5.5 | 8.0 / 7.0 / 5.5 | 8.5 / 7.0 / 6.0 |
| Exterior dimensions (H×W×D) |                       | mm     | 267×783×210             |                 |                 |                 |
| Net weight                  |                       | kg     | 7.5                     |                 |                 |                 |
| Refrigerant piping size     | Liquid / Gas          | Φmm    | 6.35(1/4") / 9.52(3/8") |                 |                 |                 |
| Clean filter                |                       |        | —                       |                 |                 |                 |

#### NOTES

•The data are measured under the following conditions(ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.  
• Sound level the value in an anechoic chamber.During operation these values are somewhat higher due to ambient conditions.