



SINGLE-SPLIT FLOOR STANDING TYPE

SRF-ZS/ZSX



SRF25,35ZS-W, 50ZSX-W

Auto air outlet selection

In case both lower and upper air outlets can be selected.



Wireless remote control



SRC25,35ZS-W2




SRC50ZSX-W2,-W3



Installation workability

Piping and drain hose connection can be selected out of 6-directions.



KEY FEATURES

- The elegant semi-flat front panel in stylish white complements various room aesthetics and creates a relaxing atmosphere
- Offers options for wall hanging, floor standing, or behind-gallery installation
- Utilizes refrigerant R32 for low Global Warming Potential (GWP) and high energy efficiency
- Operates quietly with a noise level as low as 25dB(A) in cooling Ulo mode
- Includes a "flap control system" allowing users to adjust flap angles and positions according to their preference
- Equipped with an allergen-clear filter as a default feature

SPECIFICATIONS

Indoor unit				SRF25ZS-W	SRF35ZS-W	SRF50ZSX-W
Outdoor unit				SRC25ZS-W2	SRC35ZS-W2	SRC50ZSX-W2,-W3
Power source				1 Phase, 220 - 240V, 50Hz		
Nominal cooling capacity (Min-Max)			kW	2.5 (0.9 - 3.1)	3.5 (0.9 - 4.1)	5.0 (1.1 - 5.6)
Nominal heating capacity (Min-Max)			kW	2.9 (0.8 - 3.7)	4.5 (0.8 - 5.2)	6.0 (0.8 - 7.4)
Power consumption	Cooling/Heating	kW		0.59 / 0.66	0.82 / 1.12	1.32 / 1.58
EER/COP	Cooling/Heating			4.24 / 4.39	4.27 / 4.02	3.79 / 3.80
Max. running current			A	9	9	15
Sound power level	Indoor	Cooling/Heating	dB(A)	50 / 51	51 / 52	58 / 58
	Outdoor	Cooling/Heating		59 / 60	63 / 64	63 / 62
Sound pressure level	Indoor	Cooling (Hi/Me/Lo/Ulo)	dB(A)	38 / 32 / 29 / 25	40 / 35 / 33 / 29	46 / 38 / 33 / 28
		Heating (Hi/Me/Lo/Ulo)		39 / 35 / 33 / 29	41 / 36 / 35 / 33	46 / 41 / 38 / 32
Air flow	Outdoor	Cooling/Heating		45 / 47	50 / 51	51 / 51
		Cooling (Hi/Me/Lo/Ulo)	m³/min	9.0 / 7.6 / 6.7 / 5.8	9.2 / 7.8 / 7.3 / 6.4	11.5 / 9.6 / 7.4 / 6.6
	Heating (Hi/Me/Lo/Ulo)	10.5 / 8.2 / 7.7 / 6.6		10.7 / 8.3 / 8.1 / 7.4	12.0 / 10.0 / 9.4 / 7.6	
		Outdoor	Cooling/Heating		27.4 / 27.4	31.5 / 31.5
Exterior dimensions	Indoor	Height x Width x Depth	mm	600 x 860 x 238		
	Outdoor			540 x 780(+62) x 290		
Net weight	Indoor / Outdoor	kg		18.0 / 31.0	19.0 / 34.5	19.0 / 45.0
Refrigerant	Type/GWP	kg/TCO ₂ Eq		R32 / 675		
	Charge <td>0.62 / 0.419</td> <td>0.78 / 0.527</td> <td>1.30 / 0.878</td>			0.62 / 0.419	0.78 / 0.527	1.30 / 0.878
Refrigerant piping size	Liquid/Gas	ø mm		6.35(1/4") / 9.52(3/8")		6.35(1/4") / 12.7(1/2")
Refrigerant line (one way) length [chargeless length]			m	Max.20 [10]	Max.20 [15]	Max.30 [15]
Vertical height differences			Outdoor is higher/lower	Max.10 / Max.10		Max.20 / Max.20
Outdoor operating temperature range	Cooling	°CDB	-15 to 46			
	Heating		-15 to 24			
Clean filter			Allergen Clear Filter x1, Photocatalytic Washable Deodorising Filter x1			

- The data are measured under the following conditions(ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.
- Sound level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.
- 'tonne(s) of CO₂ equivalent' means a quantity of greenhouse gases- expressed as the product of the weight of the greenhouse gases in metric tonnes and of their global warming potential.