

OUTDOOR UNITS

UNI SPLIT 2 SERIES

ECOLOGICAL
REFRIGERANT 

New generation of semi-industrial units available in capacities of 3,5 ~ 16 kW. Units with capacities of 10 kW or higher are also available in 3-phase design.

FEATURES

- Energy class A++ / A+
- Lightweight, compact design
- All capacities are single fan
- Chassis heater



NEW

ASGE-12BI2
ASGE-18BI2
ASGE-24BI2
ASGE-30BI2
ASGE-36BI2
ASGE-36BI2-3
ASGE-42BI2
ASGE-42BI2-3
ASGE-48BI2
ASGE-48BI2-3
ASGE-60BI2-3

DC INVERTER



TECHNICAL PARAMETERS

MODEL		ASGE-12BI2	ASGE-18BI2	ASGE-24BI2	ASGE-30BI2	
Capacity cooling / heating	kW	3,5 / 4,0	5,3 / 5,8	7,1 / 8,0	8,5 / 8,8	
Power supply	Phase / Hz / V	1~ / 50 / 220-240	1~ / 50 / 220-240	1~ / 50 / 220-240	1~ / 50 / 220-240	
Sound pressure level at 1 m	dB(A)	48	52	55	57	
Dimension (w x h x d) / Net weight	mm/kg	675 x 553 x 285 / 24,5	745 x 555 x 300 / 30,5	889 x 660 x 340 / 41,5	889 x 660 x 340 / 46,0	
Operating temperature range - cooling / heating	°C	-20~52 / -20~24	-20~52 / -20~24	-20~52 / -20~24	-20~52 / -20~24	

MODEL		ASGE-36BI2	ASGE-36BI2-3	ASGE-42BI2	ASGE-42BI2-3	
Capacity cooling / heating	kW	10,5 / 11,5	10,5 / 11,5	12,1 / 13,5	12,1 / 13,5	
Power supply	Phase / Hz / V	1~ / 50 / 220-240	3~ / 50 / 380-415	1~ / 50 / 220-240	3~ / 50 / 380-415	
Sound pressure level at 1 m	dB(A)	57	57	58	58	
Dimension (w x h x d) / Net weight	mm/kg	940 x 820 x 530 / 65,0	940 x 820 x 370 / 75,0	940 x 820 x 370 / 66,0	940 x 820 x 370 / 76,0	
Operating temperature range - cooling / heating	°C	-20~52 / -20~24	-20~52 / -20~24	-20~52 / -20~24	-20~52 / -20~24	

MODEL		ASGE-48BI2	ASGE-48BI2-3	ASGE-60BI2-3		
Capacity cooling / heating	kW	13,4 / 15,5	13,4 / 15,5	16,0 / 17,0		
Power supply	Phase / Hz / V	1~ / 50 / 220-240	3~ / 50 / 380-415	3~ / 50 / 380-415		
Sound pressure level at 1 m	dB(A)	59	59	60		
Dimension (w x h x d) / Net weight	mm/kg	940 x 820 x 370 / 73,0	940 x 820 x 370 / 81,0	990 x 960 x 370 / 94,0		
Operating temperature range - cooling / heating	°C	-20~52 / -20~24	-20~52 / -20~24	-20~52 / -20~24		