

SPLIT AIR CONDITIONER

TOWER SERIES

ECOLOGICAL
REFRIGERANT  R32

FEATURES

- Designed with an emphasis on aesthetics
- Usable for larger areas such as offices, meeting rooms, restaurants etc.
- Equipped with horizontal and vertical electric louver
- WiFi
- Controlled by built-in panel or remote controller (in standard)



AST-24BI
AST-48BI

DC INVERTER  **WIFI**



TECHNICAL PARAMETERS

MODEL			AST-24BI	AST-48BI	
Capacity cooling / heating	kW		7,2 / 7,9	12,5 / 13,5	
Power supply	Hz / V		1~ / 50 / 220-240	1~ / 50 / 220-240	
SEER/ SCOP	-		6,1 / 4,0	5,6 / 3,7	
Energy class cooling/ heating (Average)			A++ / A+	A+ / A	
Sound pressure level at 1 m	ID	dB(A)	45 / 41 / 38 / 35/	53 / 51 / 50 / 48	
	OD	dB(A)	61	64	
Dimension (w x h x d) / Net weight	ID	mm/kg	507 x 1770 x 320 / 38,0	587 x 1882 x 394 / 55,0	
	OD	mm/kg	965 x 700 x 396 / 53,5	1028 x 822 x 530 / 89,0	
Operating temperature range - cooling / heating	°C		-15 ~ 43 / -15 ~ 24	-15 ~ 43 / -15 ~ 24	