

FCU INDOOR UNITS

FOUR-WAY CASSETTE UNITS, 4 PIPES

FEATURES

- Independent connection to the heating and cooling circuits
- Drainage water pump included
- Fresh air connection
- Optionally Remote controller SRC-61
- Optionally wired controller SWC-61
- Optionally central controller SCM-30
- Support Modbus RTU
- Equipped with ON/OFF contact
- Possibility of using external control of fan speed (low, medium, high) by 230 V via SF2-CTK
- Possibility of using external control of fan speed (low, medium, high) by 0-10V DC via SF2-EC (require SF2-CTK)

SF2-600-1200C4



OPTIONAL
REMOTE CONTROLLER
SRC-61

TECHNICAL PARAMETERS

MODEL		SF2-600C4	SF2-700C4	SF2-800C4	SF2-1000C4
Capacity cooling / heating	kW	4,7 / 7,3	5,0 / 7,0	5,5 / 7,5	9,0 / 9,4
Power supply	phase / Hz / V	1~ / 50 / 220-240	1~ / 50 / 220-240	1~ / 50 / 220-240	1~ / 50 / 220-240
Sound pressure level at 1 m	dB(A)	34 / 32 / 29 / 26 / 24 / 22 / 20	37 / 35 / 32 / 28 / 26 / 23 / 21	41 / 39 / 36 / 32 / 29 / 26 / 23	47 / 39 / 28
Dimension (w × h × d) / Net weight	mm / kg	840 × 288 × 840 / 23,9	840 × 288 × 840 / 23,9	840 × 288 × 840 / 23,9	840 × 288 × 840 / 26,2

MODEL		SF2-1200C4			
Capacity cooling / heating	kW	10,0 / 10,8			
Power supply	phase / Hz / V	1~ / 50 / 220-240			
Sound pressure level at 1 m	dB(A)	51 / 44 / 32			
Dimension (w × h × d) / Net weight	mm / kg	840 × 288 × 840 / 26,2			

Four-way cassette with 4 pipes doesn't include 3 or 2-way valve in the package.
The valve uses the characteristics of NC (normally closed) and power supply 230V from fan coil unit. SINCLAIR doesn't offer valves.

* The decorative panel for the cassette unit is now a separate item in the price list and must be specified in the order.