

## FCU INDOOR UNITS

### FOUR-WAY CASSETTE UNITS, 2 PIPES

#### FEATURES

- Drainage water pump included
- 7 speeds of fan
- Fresh air connection
- Optionally Remote controller SRC-61
- Optionally wired controller SWC-61
- Optionally central controller SCM-30
- Support Modbus RTU
- Equipped with ON/OFF contact
- Possibility of using external control of fan speed (low, medium, high) by 230 V via SF2-CTK
- Possibility of using external control of fan speed (low, medium, high) by 0-10V DC via SF2-EC (require SF2-CTK)

SF2-600-1200C2



OPTIONAL  
REMOTE CONTROLLER  
SRC-61



#### TECHNICAL PARAMETERS

MODEL		SF2-600C2	SF2-700C2	SF2-800C2	SF2-1000C2
Capacity cooling / heating	kW	5,5 / 6,5	6,5 / 7,5	7,5 / 8,5	8,5 / 9,5
Power supply	phase / Hz / V	1~ / 50 / 220-240	1~ / 50 / 220-240	1~ / 50 / 220-240	1~ / 50 / 220-240
Sound pressure level at 1 m	dB(A)	40 / 38 / 35 / 32 / 29 / 26 / 22	37 / 35 / 32 / 29 / 26 / 24 / 21	41 / 39 / 36 / 33 / 29 / 26 / 23	47 / 45 / 42 / 38 / 35 / 31 / 27
Dimension (w × h × d) / Net weight	mm / kg	840 × 204 × 840 / 19,3	840 × 288 × 840 / 23,6	840 × 288 × 840 / 23,6	840 × 288 × 840 / 23,6

MODEL		SF2-1200C2			
Capacity cooling / heating	kW	10,5 / 12,0			
Power supply	phase / Hz / V	1~ / 50 / 220-240			
Sound pressure level at 1 m	dB(A)	52 / 49 / 47 / 44 / 41 / 37 / 32			
Dimension (w × h × d) / Net weight	mm / kg	840 × 288 × 840 / 25,9			

Four-way cassette with 2 pipes doesn't include 3 or 2-way valve in the package.  
The valve uses the characteristics of NC (normally closed) and power supply 230V from fan coil unit. SINCLAIR doesn't offer valves.

\* The decorative panel for the cassette unit is now a separate item in the price list and must be specified in the order.