

FCU INDOOR UNITS

FOUR-WAY COMPACT CASSETTE UNITS, 2 PIPES

FEATURES

- Decorative panel included
- Drainage water pump included
- Fresh air connection
- Remote controller R05 in package
- Optionally wired controller KJR-29B
- Optionally central controller SCM-30
- Optionally drip pan SDF-CC
- Support Modbus RTU
- Equipped with alarm and ON/OFF contact

SF-300-500C2M



REMOTE CONTROLLER
R05 AS STANDARD

TECHNICAL PARAMETERS

MODEL		SF-300C2M	SF-400C2M	SF-500C2M	
Capacity cooling / heating	kW	3,0 / 2,6	4,0 / 4,1	4,2 / 5,0	
Power supply	phase / Hz / V	1~ / 50 / 220-240	1~ / 50 / 220-240	1~ / 50 / 220-240	
Sound pressure level at 1 m	dB(A)	39 / 33 / 27	42 / 36 / 30	43 / 38 / 32	
Dimension (w × h × d) / Net weight	mm / kg	575 × 261 × 575 / 16,5	575 × 261 × 575 / 16,5	575 × 261 × 575 / 16,5	

Four-way cassette with 2 pipes doesn't include 3 or 2-way valve in the package.

The valve uses the characteristics of NC (normally closed) and power supply 230V from fan coil unit. SINCLAIR doesn't offer valves.