

console series



FEATURES

- Energy class A++ / A+
- Right side water outlet
- 7 speeds of fan
- Dual air outlet for heating
- Function "I FEEL"
- 8 °C heating

STANDARD ACCESSORIES

- Filters - catechin SAF-OPWC4 and active carbon filter SAF-OPWA4
- Cold plasma generator
- WiFi
- Chassis heater
- Remote controller

OPTIONAL ACCESSORIES

- Health filters
- GSM module G2S-T
- Wired controller SWC-02C, SWC-04C
- Central controller SCC-36
- Control module SCMI-03S
- BACNET gateway SBG-01
- Alarm interface SAI-01
- MODBUS control possibility via SWC-02C or SWC-04C



TECHNICAL PARAMETERS

MODEL			ASP-09BI	ASP-12BI	ASP-18BI
Capacity cooling / heating	kW		2,7 / 2,9	3,5 / 3,8	5,2 / 5,3
Power supply	Phase / Hz / V		1~ / 50 / 220-240	1~ / 50 / 220-240	1~ / 50 / 220-240
SEER / SCOP	-		7,2 / 4,0	7,0 / 4,1	6,6 / 4,1
Energy class cooling / heating (A, W, C)	-		A++ / (A+, A+++, -)	A++ / (A+, A+++, -)	A++ / (A+, A+++, -)
Sound pressure level at 1m	ID	dB(A)	39 / 36 / 33 / 31 / 29 / 26 / 23	44 / 40 / 38 / 36 / 33 / 29 / 25	47 / 45 / 42 / 40 / 37 / 35 / 31
	OD	dB(A)	49	52	57
Dimension (w x h x d) / Net weight	ID	mm/kg	700×600×215 / 15,5	700×600×215 / 15,5	700×600×215 / 15,5
	OD	mm/kg	782×540×320 / 27,5	848×596×320 / 30,5	965×700×396 / 46,0
Operating temperature range (Cool/Heat)	°C		-15~43 / -22~24	-15~43 / -22~24	-15~43 / -22~24