INDOOR UNITS COMPACT FOUR WAY CASSETTE

FEATURES

- · Very quiet operation of the device from 25dB(A)
- · Condensate pump included
- · 7 speeds of fan
- · Separate louver control 1-4
- · The units are equipped with a fresh air inlet
- Equipped with alarm and ON/OFF contact with selectable logic
- · Optionally remote controller SRC-61
- Optionally wired / group controller SWC-61, SWC-62, SWC-63



TECHNICAL PARAMETERS

MODEL		SDV6-CC15	SDV6-CC22	SDV6-CC28	SDV6-CC36	
Capacity cooling / heating	kW	1,5 / 1,8	2,2 / 2,4	2,8 / 3,2	3,6 / 4,0	
Power supply	phase / Hz / V	1~/50/220-240	1~ / 50 / 220-240	1~/50/220-240	1~/50/220-240	
Sound pressure level at 1 m	dB(A)	29 / 28 / 27 / 27 / 26 / 26 / 25	29 / 28 / 27 / 27 / 26 / 26 / 25	30 / 29 / 28 / 27 / 26 / 26 / 25	31 / 30 / 29 / 28 / 27 / 26 / 26	
Dimension (w \times h \times d) / Net weight	mm / kg	638 × 235 × 575 / 13,0	638 × 235 × 575 / 13,0	638 × 235 × 575 / 13,0	638 × 235 × 575 / 14,0	

MODEL		SDV6-CC45	SDV6-CC56	SDV6-CC63	
Capacity cooling / heating	kW	4,5 / 5,0	5,6 / 6,3	6,3 / 7,1	
Power supply	phase / Hz / V	1~/50/220-240	1~ / 50 / 220-240	1~ / 50 / 220-240	
Sound pressure level at 1 m	dB(A)	37 / 35 / 33 / 31 / 29 / 28 / 27	39 / 38 / 37 / 36 / 35 / 34 / 32	43 / 42 / 40 / 38 / 36 / 35 / 34	
Dimension (w × h × d) / Net weight	mm / kg	638 × 235 × 575 / 14,0	638 × 235 × 575 / 15,0	638 × 235 × 575 / 15,0	

^{*} The decorative panel for the cassette unit is now a separate item in the price list and must be specified in the order.

