

INDOOR UNITS

FOUR WAY CASSETTE UNITS

FEATURES

- Condensate pump included
- 7 speeds of fan
- Separate louver control 1-4
- The units are equipped with a fresh air inlet
- Equipped with alarm and ON / OFF contact with selectable logic
- Optionally remote controller SRC-61
- Optionally wired / group controller SWC-61, SWC-62, SWC-63

SDV6-CXX



TECHNICAL PARAMETERS

MODEL		SDV6-C71	SDV6-C80	SDV6-C90	SDV6-C100
Capacity cooling / heating	kW	7,1 / 8,0	8,0 / 9,0	9,0 / 10,0	10,0 / 11,0
Power supply	phase / Hz / V	1~ / 50 / 220-240	1~ / 50 / 220-240	1~ / 50 / 220-240	1~ / 50 / 220-240
Sound pressure level at 1 m	dB(A)	37 / 36 / 34 / 33 / 32 / 30 / 29	38 / 37 / 35 / 34 / 32 / 31 / 29	38 / 37 / 35 / 34 / 32 / 31 / 29	41 / 40 / 38 / 37 / 36 / 34 / 33
Dimension (w × h × d) / Net weight	mm / kg	840 × 204 × 840 / 22,0	840 × 204 × 840 / 22,0	840 × 246 × 840 / 22,0	840 × 288 × 840 / 24,0

MODEL		SDV6-C112	SDV6-C140		
Capacity cooling / heating	kW	11,2 / 12,5	14,0 / 16,0		
Power supply	phase / Hz / V	1~ / 50 / 220-240	1~ / 50 / 220-240		
Sound pressure level at 1 m	dB(A)	43 / 42 / 40 / 39 / 37 / 36 / 34	43 / 42 / 40 / 39 / 37 / 36 / 34		
Dimension (w × h × d) / Net weight	mm / kg	840 × 288 × 840 / 24,0	840 × 288 × 840 / 26,5		

* The decorative panel for the cassette unit is now a separate item in the price list and must be specified in the order.