

INDOOR UNITS FLOOR/CEILING UNITS

FEATURES

- They can be installed in a horizontal or vertical position
- Massive distribution of air to all corners of the room
- 7 speeds of fan
- Equipped with alarm and ON/OFF contact with selectable logic
- Optionally remote controller SRC-61
- Optionally wired / group controller SWC-61, SWC-62, SWC-63

SDV6-FXX



TECHNICAL PARAMETERS

MODEL		SDV6-F36	SDV6-F45	SDV6-F56	SDV6-F71
Capacity cooling / heating	kW	3,6 / 4,0	4,5 / 5,0	5,6 / 6,3	7,1 / 8,0
Power supply	phase / Hz / V	1~ / 50 / 220-240	1~ / 50 / 220-240	1~ / 50 / 220-240	1~ / 50 / 220-240
Sound pressure level at 1,4 m	dB(A)	32 / 30 / 29 / 28 / 27 / 26 / 25	36 / 35 / 34 / 33 / 32 / 31 / 30	43 / 41 / 40 / 38 / 36 / 34 / 33	43 / 40 / 39 / 37 / 35 / 34 / 33
Dimension (w × h × d) / Net weight	mm / kg	1069 × 674 × 234 / 24,7	1069 × 674 × 234 / 24,7	1069 × 674 × 234 / 24,7	1284 × 674 × 234 / 29,8

MODEL		SDV6-F80	SDV6-F90	SDV6-F100	SDV6-F112
Capacity cooling / heating	kW	8,0 / 9,0	9,0 / 10,0	10,0 / 11,2	11,2 / 12,5
Power supply	phase / Hz / V	1~ / 50 / 220-240	1~ / 50 / 220-240	1~ / 50 / 220-240	1~ / 50 / 220-240
Sound pressure level at 1,4 m	dB(A)	45 / 44 / 42 / 40 / 38 / 36 / 34	48 / 47 / 46 / 44 / 42 / 40 / 37	42 / 40 / 39 / 37 / 35 / 33 / 32	44 / 42 / 41 / 39 / 37 / 35 / 33
Dimension (w × h × d) / Net weight	mm / kg	1284 × 674 × 234 / 29,8	1284 × 674 × 234 / 29,8	1649 × 674 × 234 / 36,4	1649 × 674 × 234 / 36,4

MODEL		SDV6-F125	SDV6-F140		
Capacity cooling / heating	kW	12,5 / 14,0	14,0 / 16,0		
Power supply	phase / Hz / V	1~ / 50 / 220-240	1~ / 50 / 220-240		
Sound pressure level at 1,4 m	dB(A)	49 / 48 / 46 / 44 / 42 / 40 / 38	52 / 50 / 48 / 46 / 44 / 42 / 40		
Dimension (w × h × d) / Net weight	mm / kg	1649 × 674 × 234 / 36,4	1649 × 674 × 234 / 36,4		