

INDOOR UNITS WALL MOUNTED UNITS

FEATURES

- Design unit with built-in display
- 7 speeds of fan
- Possibility to install 30mm below the ceiling
- Equipped with alarm and ON/OFF contact with selectable logic
- Optionally remote controller SRC-61
- Optionally wired / group controller SWC-61, SWC-62, SWC-63

SDV6-HXXS



SDV6-HFXXS



TECHNICAL PARAMETERS

MODEL		SDV6-H(F)15S	SDV6-H(F)22S	SDV6-H(F)28S	SDV6-H(F)36S
Capacity cooling / heating	kW	1,5 / 1,8	2,2 / 2,4	2,8 / 3,2	3,6 / 4,0
Power supply	phase / Hz / V	1~ / 50 / 220-240	1~ / 50 / 220-240	1~ / 50 / 220-240	1~ / 50 / 220-240
Sound pressure level at 1 m	dB(A)	32 / 31 / 30 / 30 / 29 / 28 / 27	33 / 32 / 31 / 30 / 29 / 28 / 27	35 / 34 / 33 / 32 / 31 / 30 / 28	37 / 36 / 34 / 33 / 31 / 30 / 28
Dimension (w × h × d) / Net weight	mm / kg	750 × 295 × 265 / 9,0	750 × 295 × 265 / 9,0	750 × 295 × 265 / 10,0	750 × 295 × 265 / 10,0

MODEL		SDV6-H(F)45S	SDV6-H(F)56S	SDV6-H71S	SDV6-H80S
Capacity cooling / heating	kW	4,5 / 5,0	5,6 / 6,3	7,1 / 8,0	8,0 / 9,0
Power supply	phase / Hz / V	1~ / 50 / 220-240	1~ / 50 / 220-240	1~ / 50 / 220-240	1~ / 50 / 220-240
Sound pressure level at 1 m	dB(A)	37 / 35 / 33 / 32 / 31 / 30 / 29	41 / 39 / 37 / 35 / 33 / 31 / 29	44 / 42 / 40 / 38 / 36 / 34 / 32	45 / 43 / 41 / 39 / 37 / 35 / 32
Dimension (w × h × d) / Net weight	mm / kg	950 × 295 × 265 / 11,5	950 × 295 × 265 / 11,5	1200 × 295 × 265 / 15,0	1200 × 295 × 265 / 15,0

SDV6-HFxxS use flat panel which require space 90mm below the ceiling.