

RM_MUT COMPACT 4-WAY CASSETTE

The compact 4 way cassette has been especially designed for small commercial application where a compact efficient unit is needed.

Design

- Elegant and Flat appearance
- Fit within the T-bar of grid ceiling : 620mm X 620mm.

Comfort

- Individual setting of louver position: 3 different swing mode: standard, diagonally, opposite, turn around.
- 5 steps air flow.

Easy to install

- Compact and thin chassis with only 256mm height
- Built-in high-lift drain pump
- Light-weight unit, for easy and quick installation.



SCOP MAX



4.60

CAPACITY



2.5kW > 6kW

OPERATION



-27°C > +52°C

Occupancy sensor switches off automatically the unit if nobody is in the room to save energy.



INDOOR UNITS

RAV-RM301MUT-E/TR
RAV-RM401MUT-E/TR
RAV-RM561MUT-E/TR

SDI



OUTDOOR UNITS

RAV-GP561ATP-E/TR

DI



RAV-GM301ATP-E/TR
RAV-GM401ATP-E/TR
RAV-GM561ATP-E/TR



REMOTE CONTROLS

RBC-AXU31UM-E
RBC-AXU31-E



RBC-AMSU51E-ES(EN)
RBC-AMTU31-E
RBC-ASCU11-E

COMPACT 4-WAY CASSETTE

COMPACT 4-WAY CASSETTE Performance data with Super Digital Inverter Series 1

Outdoor unit		RAV-GP561ATP-E/TR	
Indoor unit (600X600 Cassette)		RAV- RM561MUT-E/TR	
Cooling capacity	kW	5.0	
Cooling range (min. - max.)	kW	1,2 - 5,6	
Power input (min. - rated - max.)	kW C	0,19 - 1,56 - 1,97	
EER		3,21	
SEER		6,02	
Energy efficiency class	C	A+	
Seasonal electricity consumption	kWh/a C	291	
Heating capacity	kW	5.6	
Heating range (min. - max.)	kW	0,9 - 7,0	
Power input (min. - rated - max.)	kW H	0,16 - 1,60 - 2,36	
COP	W/W	3,50	
SCOP		4,30	
Energy efficiency class	H	A+	
Seasonal electricity consumption	kWh/a H	1237	

COMPACT 4-WAY CASSETTE Performance data with Digital Inverter Series 1

Outdoor unit		RAV-GM301ATP-E/TR		RAV-GM401ATP-E/TR		RAV-GM561ATP-E/TR	
Indoor unit (600X600 Cassette)		RAV- RM301MUT-E/TR		RAV- RM401MUT-E/TR		RAV- RM561MUT-E/TR	
Cooling capacity	kW	2.5		3.6		5.0	
Cooling range (min. - max.)	kW	0.9 - 3.0		0.9 - 4.0		1.5 - 5.6	
Power input (min. - rated - max.)	kW C	0,25 - 0,59 - 0,82		0,18 - 0,90 - 2,00		0,30 - 1,64 - 1,86	
EER		4,24		4,00		3,05	
SEER		5,94		5,76		5,69	
Energy efficiency class	C	A+		A+		A+	
Seasonal electricity consumption	kWh/a C	147		219		307	
Heating capacity	kW	3.4		4.0		5.3	
Heating range (min. - max.)	kW	0.8 - 4.5		0.8 - 5.0		1.5 - 6.3	
Power input (min. - rated - max.)	kW H	0,17 - 0,76 - 1,40		0,14 - 0,95 - 1,70		0,30 - 1,47 - 2,40	
COP	W/W	4,47		4,21		3,61	
SCOP		4,70		4,44		4,37	
Energy efficiency class	H	A++		A+		A+	
Seasonal electricity consumption	kWh/a H	685		851		897	

COMPACT 4-WAY CASSETTE Physical data indoor

Indoor unit		RAV- RM301MUT-E/TR		RAV- RM401MUT-E/TR		RAV- RM561MUT-E/TR	
Air flow (H/L)	m³/h - l/s	640/440 - 177/122		660/468 - 183/130		798/546 - 221/152	
Sound pressure level (H-M-L)	dB(A)	38 - 36 - 30		41 - 36 - 32		44 - 39 - 35	
Sound power level (H-M-L)	dB(A)	53 - 51 - 45		56 - 51 - 47		59 - 54 - 50	
Dimensions (HxWxD)	mm	256 x 575 x 575		256 x 575 x 575		256 x 575 x 575	
Weight	kg	15		15		15	
Panel dimensions (HxWxD)	mm	12 x 620 x 620		12 x 620 x 620		12 x 620 x 620	
Panel weight	kg	2,5		2,5		2,5	

C: cooling mode
H: heating mode
H-M-L: High - Medium - Low speed