

HAORI / Set



- › DESIGN Line with innovative textile cover
- › A+++ for cooling & heating
- › Dust filter, ozone air purifier, and ultra pure filter
- › WiFi module integrated as standard
- › Energy monitoring: for single and multi-split systems



INDOOR UNIT			RAS-B10N4KVRG-E1 RAS-10J2AVSG-E1	RAS-B13N4KVRG-E RAS-13J2AVSG-E1	RAS-B16N4KVRG-E RAS-16J2AVSG-E1
Cooling capacity	kW	❄️	2,50	3,50	4,60
Cooling range (min.-max.)	kW	❄️	0,89 - 3,20	1,00 - 4,10	1,20 - 5,30
Power consumption (min./nom./max.)	kW	❄️	0,19/0,54/0,79	0,25/0,80/1,12	0,34/1,35/1,72
Energy efficiency EER	W/W	❄️	4,63	4,38	3,41
Energy efficiency SEER		❄️	8,60	8,70	7,80
Energy efficiency class		❄️	A+++	A+++	A++
Outdoor temperature operating range (min.-max.)	°C	❄️	-15/+46	-15/+46	-15/+46
Heating capacity	kW	🔥	3,20	4,20	5,50
Heating range (min.-max.)	kW	🔥	0,90 - 4,70	1,00 - 5,30	1,10 - 6,30
Power consumption (min./nom./max.)	kW	🔥	0,18/0,74/1,23	0,20/1,08/1,55	0,30/1,52/1,90
Energy efficiency COP	W/W	🔥	4,32	3,89	3,62
Energy efficiency SCOP		🔥	5,10	5,10	4,60
Energy efficiency class		🔥	A+++	A+++	A++
Outdoor temperature operating range (min.-max.)	°C	🔥	-15/+24	-15/+24	-15/+24
Power supply	V/Ph+N/Hz		220-240/1+N/50	220-240/1+N/50	220-240/1+N/50
Recommended fusing	A		10	10	10
Set price	€		1.830,-	2.110,-	2.435,-

INDOOR UNIT		RAS-B10N4KVRG-E1	RAS-B13N4KVRG-E	RAS-B16N4KVRG-E
Airflow	m³/h	300-600	320-670	340-730
Sound pressure level (low/med/high)	dB(A) ❄️	19/-/41	19/-/43	21/-/45
Sound pressure level (low/med/high)	dB(A) 🔥	19/-/41	19/-/43	22/-/45
Dimensions (HxWxD)	mm	300 x 987 x 210	300 x 987 x 210	300 x 987 x 210
Weight	kg	11	11	12
Price	€	880,-	960,-	1.015,-

OUTDOOR UNIT		RAS-10J2AVSG-E1	RAS-13J2AVSG-E1	RAS-16J2AVSG-E1
Sound pressure level (low/med/high)	dB(A) ❄️	37/-/44	39/45/46	40/47/48
Sound pressure level (low/med/high)	dB(A) 🔥	39/-/46	43/46/48	43/49/50
Suction gas pipe diameter	mm (inch)	9,5 (3/8)	9,5 (3/8)	12,7 (½)
Liquid pipe diameter	mm (inch)	6,3 (¼)	6,3 (¼)	6,3 (¼)
Pipe length (min.)	m	2	2	2
Pipe length (max.)	m	20	20	20
Height difference (max.)	m	12	12	12
Compressor type		DC Rotary	DC Rotary	DC Rotary
Refrigerant		R32	R32	R32
Refrigerant charge	kg	0,55	0,80	0,80
Dimensions (HxWxD)	mm	550 x 780 x 290	550 x 780 x 290	550 x 780 x 290
Weight	kg	26	30	33
Price	€	950,-	1.150,-	1.420,-

ACCESSORIES	DESCRIPTION	INCLUDED	PRICE €
RB-RXS34-E	Design infrared remote control, black, with magnetic holder	✓	
RB-RXS33-E	Infrared remote control including weekly timer and 8°C frost protection function		105,-
RB-I4101-E	Fabric cover Dark Gray enclosed	✓	
RB-I4102-E	Fabric cover Light Gray enclosed	✓	
RB-I4103-E	Fabric cover Bluish Gray		125,-
RB-I4104-E	Fabric cover Gray Beige		125,-
RB-I4105-E	Fabric cover Dark Brown		125,-
RB-I4106-E	Fabric cover Emerald Blue		125,-
818F0050	Ultra-pure 2.5 filter strips	✓	
818F0023	Active carbon-catechin filter strips		30,-
818F0036	IAQ filter strips		50,-
818F0072	Ultra-Fresh filter strips		35,-
TCB-IFCB5-PE	External on/off PCB, window contact module		80,-
TCB-PX100-PE	Casing for outdoor installation of window contact module for high-wall units		95,-

You will find all the control options on page 33.