

4-way SMART cassette

- › 4-way high-efficiency design for large capacities
- › Enhanced energy savings via presence sensor option
- › Integrated drain pump (850 mm); prepared for external fresh air supply
- › Not a stock item – lead time on request
 - › Accessories required: remote control + panel



INDOOR UNIT		MMU-UP0091H-E	MMU-UP0121H-E	MMU-UP0151H-E	MMU-UP0181H-E	MMU-UP0241H-E
Cooling capacity	kW ❄️	2,80	3,60	4,50	5,60	7,10
Heating capacity	kW 🔥	3,20	4,00	5,00	6,30	8,00
Airflow	m³/h	708/738/ 768/792/ 846	708/738/ 768/792/ 846	800/860/ 920/960/ 1060	940/1040/ 1100/1160/ 1260	1120/1210/ 1300/1440/ 1580
Sound pressure level (low/med/high)	dB(A) ❄️	26/28/30	26/28/30	28/30/32	31/33/36	35/37/41
Liquid pipe diameter	mm (inch)	6,4 (¼)	6,4 (¼)	6,4 (¼)	6,4 (¼)	9,5 (3/8)
Suction gas pipe diameter	mm (inch)	9,5 (3/8)	9,5 (3/8)	12,7 (½)	12,7 (½)	15,9 (5/8)
Condensate pipe diameter	mm	25	25	25	VP25 (25/32)	VP25 (25/32)
Power supply	V/Ph+N/Hz	220-240/1+N/ 50	220-240/1+N/ 50	220-240/1+N/ 50	220-240/1+N/ 50	220-240/1+N/ 50
Power consumption (min./nom./max.)	kW ❄️	0,02	0,02	0,018	0,026	0,042
Dimensions (HxWxD)	mm	256 x 840 x 840	256 x 840 x 840	319 x 840 x 840	319 x 840 x 840	319 x 840 x 840
Weight	kg	18	18	25	25	25
Panel dimensions (HxWxD)	mm	30 x 950 x 950	30 x 950 x 950	30 x 950 x 950	30 x 950 x 950	30 x 950 x 950
Panel weight	kg	5,0	5,0	5,0	5,0	5,0
Price	€	2.015,-	2.205,-	2.465,-	2.625,-	2.730,-

INDOOR UNIT		MMU-UP0271H-E	MMU-UP0301H-E	MMU-UP0361H-E	MMU-UP0481H-E	MMU-UP0561H-E
Cooling capacity	kW ❄️	8,00	9,00	11,20	14,00	16,00
Heating capacity	kW 🔥	9,00	10,00	12,50	16,00	18,00
Airflow	m³/h	1250/1320/ 1380/1590/ 1770	1400/1450/ 1520/1770/ 1940	1260/1356/ 1596/1848/ 2184	1368/1470/ 1740/1998/ 2262	1404/1512/ 1782/2034/ 2262
Sound pressure level (low/med/high)	dB(A) ❄️	35/37/42	37/39/44	32/38/45	33/39/46	35/40/46
Liquid pipe diameter	mm (inch)	9,5 (3/8)	9,5 (3/8)	9,5 (3/8)	9,5 (3/8)	9,5 (3/8)
Suction gas pipe diameter	mm (inch)	15,9 (5/8)	15,9 (5/8)	15,9 (5/8)	15,9 (5/8)	15,9 (5/8)
Condensate pipe diameter	mm	VP25 (25/32)	VP25 (25/32)	25	25	VP25 (25/32)
Power supply	V/Ph+N/Hz	220-240/1+N/ 50	220-240/1+N/ 50	220-240/1+N/ 50	220-240/1+N/ 50	220-240/1+N/ 50
Power consumption (min./nom./max.)	kW ❄️	0,054	0,068	0,125	0,135	0,137
Dimensions (HxWxD)	mm	319 x 840 x 840	319 x 840 x 840	319 x 840 x 840	319 x 840 x 840	319 x 840 x 840
Weight	kg	25	25	25	25	25
Panel dimensions (HxWxD)	mm	30 x 950 x 950	30 x 950 x 950	30 x 950 x 950	30 x 950 x 950	30 x 950 x 950
Panel weight	kg	5,0	5,0	5,0	5,0	5,0
Price	€	2.775,-	2.855,-	2.960,-	3.120,-	3.365,-

ACCESSORIES	DESCRIPTION	PRICE €
RBC-U41PG(W)-E	Panel for smart cassette	430,-
RBC-AXU41U-E	Infrared remote control + receiver kit for installation in VRF TU2C Smart Cassette	315,-
TCB-SIR41U-E	Occupancy sensor kit for installation in smart cassette	130,-
TCB-GFC1603UE	Fresh air filter	290,-
TCB-SP1603UE	Spacer frame for lowering the panel by 70 mm	230,-
TCB-BC1603UE	Air discharge direction kit for blocking of up to three discharge sides	75,-
TCB-FF101URE2	Spigot flange for fresh air connection Ø 100 mm	80,-

You will find all the control options from page 183 onwards.

BUSINESS / VRF IDU

